

NO. OF COPIES RECEIVED			
DISTRIBUTION			
TO			
BY			
DATE			
OFFICE			
OF			

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Superseded (Old)
C-102 and C-101
Effective 1-1-65

5a. Indicate Type of Lease
State ☐ Fee ☒
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.

1. <input type="checkbox"/> OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER		7. Unit Agreement Name
2. Name of Operator Joel B. Burr, Jr.		8. Farm or Lease Name Foothills B
3. Address of Operator 300 W. Arrington, Suite 300, Farmington, NM 87401		9. Well No. 1
4. Location of Well UNIT LETTER <u>J</u> <u>1390</u> FEET FROM THE <u>SOUTH</u> LINE AND <u>1650</u> FEET FROM THE <u>EAST</u> LINE, SECTION <u>20</u> TOWNSHIP <u>30N</u> RANGE <u>12W</u> NMPM.		10. Field and Pool, or Wildcat Undesignated Fruitland
15. Elevation (Show whether DF, RT, GR, etc.) 5620 GR		12. County San Juan

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	
		OTHER <u>Fracture Treatment</u>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Perforate Pictured Cliffs zone 1723-31 at 2 shots per foot. Fracture interval with 31,250 gallons 70% foam and 30,000# 10/20 sand. Tested at 265 MCF gas daily and large amount of water. Set cast iron plug at 1650' and pressure tested to 3000 psi. Perforate Fruitland 1373-1383. Fracture with 22,734 gallons 70 foam and 12,400# 10/20 sand. Job complete 4/25/84.

RECEIVED

MAY 16 1984

OIL CON. DIV.
DIST. 3

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED John Alexander TITLE AGent DATE 5/11/84

APPROVED BY Frank J. Chung TITLE SUPERVISOR DISTRICT # 3 DATE MAY 16 1984

CONDITIONS OF APPROVAL, IF ANY:

