

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN DUPLICATE*

(See other in-
structions on
reverse side)Form approved.
Budget Bureau No. 42-R355.5.

WELL COMPLETION OR RECOMPLETION REPORT AND LOG*

1a. TYPE OF WELL: OIL WELL ☐ GAS WELL ☒ DEEP-SEA ☐ OTHER ☐
b. TYPE OF COMPLETION: NEW WELL ☒ WORK OVER ☐ DEEP-EN ☐ PLUG BACK ☐ DIFF. RESVR. ☐

2. NAME OF OPERATOR

Southland Royalty Company

3. ADDRESS OF OPERATOR

P. O. Drawer 570, Farmington, New Mexico 87499

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)*

At surface 790' FSL & 1090' FEL

At top prod. interval reported below

At total depth

BUREAU OF LAND MANAGEMENT
FARMINGTON RESOURCE AREA

11. PERMIT NO.

DATE ISSUED

5. LEASE DESIGNATION AND SERIAL NO.

SF-078198

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Nye

9. WELL NO.

14A

10. FIELD AND POOL, OR WILDCAT

Blanco Mesaverde

11. SEC., T., R., M., OR BLOCK AND SURVEY OR AREA

Section 13, T30N, R11W

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

15. DATE SPUDDED 6-08-84 16. DATE T.D. REACHED 6-15-84 17. DATE COMPL. (Ready to prod.) 8-19-84 18. ELEVATIONS (OF, RKB, RT, GR, ETC.)* 6152' KB 19. ELEV. CASINGHEAD 6140' GL

20. TOTAL DEPTH, MD & TVD 5240' 21. PLUG, BACK T.D., MD & TVD 5195' 22. IF MULTIPLE COMPL., HOW MANY* 23. INTERVALS DRILLED BY 0-5240' 24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD)* 4938'-5160'

25. WAS DIRECTIONAL SURVEY MADE

Deviational

26. TYPE ELECTRIC AND OTHER LOGS RUN

CDL, Induction Logs and CBL

27. WAS WELL CORED

NO

28. CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
9-5/8"	32.30#, H-40	214.73'	12-1/4"	***See other side for cement records***	
7"	20#, K-55	2805'	8-3/4"		

29. LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)	PACKER SET (MD)
4-1/2"	2639'	5197'	320 sacks (467 cu.ft.)		2-3/8"	4989'	---

31. PERFORATION RECORD (Interval, size and number)

Mesaverde - 14 holes:

4938', 4946', 4958', 4963', 4969', 4976',
4981', 4986', 4992', 5000', 5004', 5047',
5051', 5160'

32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED
4938'-5160'	Fraced with 86,300 gals fresh water and 60,000# of 20/40 sand.

33.* PRODUCTION

DATE FIRST PRODUCTION		PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump)				WELL STATUS (Producing or shut-in)	
8-27-84		Flowing				Shut-In	
DATE OF TEST	HOURS TESTED	CHOKE SIZE	PROD'N. FOR TEST PERIOD	OIL—BBL.	GAS—MCF.	WATER—BBL.	GAS-OIL RATIO
8-27-84	3	3/4"	→	----	336	-----	-----
FLOW. TUBING PRESS.	CASING PRESSURE	CALCULATED 24-HOUR RATE	OIL—BBL.	GAS—MCF.	WATER—BBL.	OIL GRAVITY-API (CORR.)	
222	537	→	----	2681	----	-----	

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)

To be sold

TEST WITNESSED BY

Steve Kellenaers

35. LIST OF ATTACHMENTS

ACCEPTED FOR RECORD

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED

Catherine J. Grayson

TITLE

Secretary

DATE

SEP 14 1984

*(See Instructions and Spaces for Additional Data on Reverse Side)

FARMINGTON RESOURCE AREA

BY

Smm

INSTRUCTIONS

General: This form is designed for submitting a complete and correct well completion report and log on all types of lands and leases to either a Federal agency or a State agency, or both, pursuant to applicable Federal and/or State laws and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office. See instructions on items 22 and 24, and 33, below regarding separate reports for separate completions.

If not filed prior to the time this summary record is submitted, copies of all currently available logs (drillers, geologists, sample and core analysis, all types electric, etc.), formation and pressure tests, and directional surveys, should be attached hereto, to the extent required by applicable Federal and/or State laws and regulations. All attachments should be listed on this form, see item 35.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 18: Indicate which elevation is used as reference (where not otherwise shown) for depth measurements given in other spaces on this form and in any attachments.

Items 22 and 24: If this well is completed for separate production from more than one interval zone (multiple completion), so state in item 22, and in item 24 show the producing interval, or intervals, top(s), bottom(s) and name(s) (if any) for only the interval reported in item 33. Submit a separate report (page) on this form, adequately identified, for each additional interval to be separately produced, showing the additional data pertinent to such interval.

Item 29: "Sacks Cement": Attached supplemental records for this well should show the details of any multiple stage cementing and the location of the cementing tool.

Item 33: Submit a separate completion report on this form for each interval to be separately produced. (See instruction for items 22 and 24 above.)

Item 28 & 29: 9-5/8" casing cemented with 110 sack s(130 cu.ft.) of C1 B w/1/4# flocele/sx & 3% CaCl2. PD @ 7:45 AM 6-8-84
 Cmt circ to surf. 7" csg cmtd w/210 sxs (353 cu.ft.) of C1 H 65/35 Poz w/3% gel, 12.5# gilsonite/sx, 10% salt & 10% CalSeal, tailed w/50 sxs (60 cu.ft.) of C1 B w/2% CaCl2. PD @ 4:00 AM 6-11-84. Good circ. Ran temp. survey TOC @ 900'.
 4-1/2" csg cmtd w/320 sxs (467 cu.ft.) of C1 b 50/50 Poz w/6% gel, 1/4# flocele/sx, & .6% Halad 9. PD @ 4:00 AM 6-17-84.
 Circ 5 bbls off top liner.

37. SUMMARY OF POROUS ZONES:

SHOW ALL IMPORTANT ZONES OF POROSITY AND CONTENTS THEREOF: CORED INTERVALS; AND ALL DRILL-STEM TESTS, INCLUDING DEPTH INTERVAL TESTED, CUSHION USED, TIME TOOL OPEN, FLOWING AND SHUT-IN PRESSURES, AND RECOVERIES

FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	38. GEOLOGIC MARKERS		
				NAME	MEAS. DEPTH	TRUE VERT. DEPTH
ESTIMATED Ojo Alamo Fruitland Pictured Cliffs Cliff House Point Lookout	1350'					
	2292'					
	2597'					
	4290'					
	4950'					