

submitted in lieu of Form 3160-5

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

1. Type of Well  
GAS

2. Name of Operator  
**BURLINGTON  
RESOURCES** OIL & GAS COMPANY

3. Address & Phone No. of Operator  
PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M  
790' FSL, 1090' FEL, Sec. 13, T-30-N, R-11-W, NMPM

5. Lease Number  
SF-078198

6. If Indian, All. or  
Tribe Name

7. Unit Agreement Name

8. Well Name & Number  
Nye #14A

9. API Well No.  
30-045-25935

10. Field and Pool  
Blanco Mesaverde

11. County and State  
San Juan Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission	Type of Action	
<input type="checkbox"/> Notice of Intent	<input type="checkbox"/> Abandonment	<input type="checkbox"/> Change of Plans
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion	<input type="checkbox"/> New Construction
<input type="checkbox"/> Final Abandonment	<input type="checkbox"/> Plugging Back	<input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> Water Shut off
	<input type="checkbox"/> Altering Casing	<input type="checkbox"/> Conversion to Injection
	<input checked="" type="checkbox"/> Other - Payadd	

13. Describe Proposed or Completed Operations

6-8-00 MIRU. ND WH. NU BOP. TIH, tag PBTD @ 5195'. TOOH w/2 3/8" tbq. TIH w/CIBP, set @ 4150'. PT csg & CIBP to 3000 psi, OK. Perf lwr Lewis @ 3790-3800', 3834-3844', 3872-3882', 3944-3954', 4004-4014', 4075-4085' w/60 0.30" diameter holes. SDON.

6-9-00 Brk dwn perfs w/666 gals 10% acetic acid. Frac lwr Lewis perfs w/5000 gal 80 quality foam pad, 20# lnr gel, 100,000# 20/40 Brady sand, 46,000 SCF N2. Flow back well.

6-10-00 TIH w/CIBP, set @ 3772'. PT CIBP to 3000 psi, OK. Perf upper Lewis @ 3426-3436', 3520-3530', 3574-3584', 3641-3651', 3680-3690', 3712-3722' w/60 0.30" diameter holes. Brk dwn perfs w/666 gals 10% acetic acid. Frac upper Lewis perfs w/5000 gal 80 quality foam pad, 20# lnr gel, 100,000# 20/40 Brady sand, 43,500 SCF N2. Flow back well.

6-11-00 Flow back well.

6-12-00 TIH w/mill. Blow well & CO to CIBP @ 3772'.

6-13-00 Mill up CIBP @ 3772'. Blow well & CO.

Continued on back

14. I hereby certify that the foregoing is true and correct.

Signed [Signature] Title Regulatory Supervisor Date 7/13/00

(This space for Federal or State Office use)

APPROVED BY \_\_\_\_\_ Title \_\_\_\_\_ Date \_\_\_\_\_

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NMOCB

ACCEPTED FOR RECORD

JUL 14 2000

OFFICE

6-14-00 Blow well & CO.  
6-15-00 Blow well & CO to CIBP @ 4150'. Mill up CIBP @ 4150'. CO to PBTD @  
5195'. SDON.  
6-16-00 TOOH w/mill. TIH w/160 jts 2 3/8" 4.7# J-55 tbgs, set @ 5143'. ND BOP.  
NU WH. RD. Rig released.