Form 3160-5	UNITED	STATES	SUBMIT IN TRIPLICA	TM7 Everience	proved. Bureau No. 1004-0135 August 31, 1985	
(Nyvember 1983) (Formerly 9-331)	DEPARTMENT OF	THE INTERIO	(Other instructions on verse side)		NATION AND BERIAL HO.	
	BUREAU OF LAN	D MANAGEMENT	/	NM 1527		
SU (Do not use th	NDRY NOTICES AN is form for proposals to drill of Use "APPLICATION FOR P	to deepen or plug back	to a different reservoir.	6. IF INDIAN, A	LLOTTER OR TRISE NAME	
1. Ott. (7) GAB				7. UNIT AGREEM	ENT NAME	
WELL WELL 2. NAME OF OPERATOR	X OTHER			8. FARM OR LE	SE NAME	
Robert L. Bayless					Coolidge Com	
3. ADDRESS OF OPERAT				9. WELL NO.		
P.O.	Box 168, Farmingto Report location clearly and in	n, NM 87499	te regulrements •	#1	POOL, OR WILDCAT	
See also space 17 bo At surface	-low.)		ECEIVE	Basin D	akota M., OR BLK. AND	
950'	FNL & 1190' FEL		FEB 01 1985	Sec 22		
14. PERMIT NO.		Show whether by A	MINETON DESCURCE	San Jua	•	
15.			ure of Notice, Report, o		TICH MANAGE	
	NOTICE OF INTENTION TO:	1	8 U	SEQUENT REPORT OF:		
TEST WATER SHUT	OFF PULL OR ALTE	L CASING	WATER SHUT-OFF	REPA	IRING WELL	
FRACTURE TREAT	MULTIPLE COM	PLETE	FRACTURE TREATMENT	ALTE	BING CASING	
SHOOT OR ACIDIZE	ABANDON®		shooting or acidizing		DONMENT*	
REPAIR WELL	CHANGE PLANS		(Nors: Report re	sults of multiple comp	pletion on Well	
(Other)	OR COMPLETED OPERATIONS (Clea	rly state all pertinent de		ompletion Report and ates, including estima		
2-1-85	Amend page 2 of as on attached		January 31, 1985.	FEB 1		
SIGNED CONTROL (This space for Fed	t the foregoing is true and cor N A . M C leral or State office use) APPROVAL, IF ANY:	rectTITLE PetroTITLE	leum Engineer	DATE	2-1-85 R-RECORD	
				tAkwingjuji nac	OUNCE AREA	

*See Instructions on Reverse Side

NMOCC

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

Robert L. Bayless Coolidge Com #1 Sundry Report Page 2

1-30-85 Ran 148 jts $4\frac{1}{2}$ " 11.6#/ft J-55 new casing as follows:

DESCRIPTION	LENGTH	DEPTH
KB to landing point 101 jts 4½" 11.6#/ft J-55 new casing D.V. Tool 46 jts 4½" 11.6#/ft J-55 new casing 1 4½" Differential Fill Float Collar 1 jt 4½" 11.6#/ft J-55 casing 1 4½" Cement Filled GuideShoe	10.00 4201.14 2.40 1924.45 2.10 42.13	0-10 10-4211 4211-4213 4213-6138 6138-6140 6140-6182 6182-6183
	6183.07	

Casing landed @ 6183 RKB. DFFC @ 6138 and D.V. Tool @4211'

Rig up Dowell, pump 10 bbls water ahead: cement 1st stage with $258~\rm{ft}^3$ Class B w/2% D-79 followed by 22l ft 3 50-50 pozmix w/2% gel and 10% salt. Good circulation throughout job. Plug did not bump. Plug down @ 10:45 p.m. 1-30-85. D.V. tool opened @ 1500 psi. Circulated mud 3 hours.

1-31-85 Completed 3 hour circulation. Pump 10 bbls water ahead: Cement 2nd stage with 1339 ft Class B w/2% D-79. Good circulation throughout job. Circulated cement to surface. Bumped plug to 2500 psi. Plug down @ 2:45 a.m. 1-31-85.