

5 BLM

UNITED STATES 1 File

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved
Budget Bureau No. 1004-0135
Expires August 31, 1985

DEPARTMENT OF THE INTERIOR

1 Celsius- Denver BUREAU OF LAND MANAGEMENT 1 Celsius-SLC

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT--" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER	RECEIVED SEP 4 1985 BUREAU OF LAND MANAGEMENT FARMINGTON RESOURCE AREA
2. NAME OF OPERATOR DUGAN PRODUCTION CORP.	
3. ADDRESS OF OPERATOR P O Box 208, Farmington, NM 87499	
4. LOCATION OF WELL (Report location clearly and in accordance with BLM Form 3160-5, Rev. 1-85. See also space 17 below.) At surface 990' FSL - 890' FEL	
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.) 5448' GL; 5460' RKB

5. LEASE DESIGNATION AND SERIAL NO. NM 16765	
6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
7. UNIT AGREEMENT NAME	
8. FARM OR LEASE NAME Nice	
9. WELL NO. 1	
10. FIELD AND POOL, OR WILDCAT Basin Dakota	
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 7, T30N, R14W, NMPM	
12. COUNTY OR PARISH San Juan	13. STATE NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREAT

MULTIPLE COMPLETE

FRACTURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON*

SHOOTING OR ACIDIZING

ABANDONMENT*

REPAIR WELL

CHANGE PLANS

(Other)

Spud & Surface Casing

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markets and zones pertinent to this work.)*

M.I. & R.U. Four Corners Drilling Company rig #3. Spudded 12 1/4" hole at 12:30 PM 8-31-85. Drilled to 225'. Ran 7 jts. 8-5/8" OD, 24#, J-55, 8 Rd ST&C casing (T.E. 207.67') set at 220' RKB. Cemented with 135 sx class "B" plus 2% CaCl₂ (159 cf). P.O.B. at 6:30 PM 8-31-85. Circulated approximately 1 1/2 bbls cement to surface. Pressure tested surface casing and BOP 750 psi for 30 minutes.

RECEIVED
SEP 06 1985
OIL CO. OF N.M.
DRI. 3

18. I hereby certify that the foregoing is true and correct

SIGNED

Jim L. Jacobs

TITLE

Geologist

DATE 9-3-85

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

SEP 04 1985

*See Instructions on Reverse Side

NMOCC

FARMINGTON RESOURCE AREA
BY 06 B