

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

5. LEASE DESIGNATION AND SERIAL NO.

SF 078125B

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Pierce A

9. WELL NO.

4

10. FIELD AND POOL, OR WILDCAT

Basin Dakota

11. SEC. T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 13, T-30-N, R-10-W
N.M.P.M.

12. COUNTY OR PARISH

San Juan

13. STATE

NM

RECEIVED

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6302' GL

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

BUREAU OF LAND MANAGEMENT

FARMINGTON RESOURCES AREA

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

Running Casing

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

12-10-85 TD 3315'. Ran 75 jts. 7", 20.0#, K-55 casing 3301' set @ 3313'. Cemented with 199 sks. Class "B", 65/35 POZ mix, 6% gel, 2% calcium chloride, 1/2 cu ft Perlite/sk (384 cu.ft.) followed by 100 sks class B, 2% calcium chloride (118 cu ft). WOC 12 hours. Held 1200#/30 minutes. Top of cement @ 1250'.

12-15-85 TD 7552'. Ran 240 jts. 4 1/2", 10.5 & 11.6#'s, K-55 casing 7540' set @ 7552'. Float collar set at 7543'. Cmt'd w/246 sks class B, 8% gel, 1/4# cu ft fine Gilsonite/sk, 0.4% HR-7 (534 cu ft), followed by 100 class B, 1/4# fine tuf-plug/sk 0.4% HR-7 (118 cu ft). WOC 18 hrs. Top of cement set @ 2700'.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Drilling Clerk

DATE

12-16-85

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side