

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

1. Type of Well

GAS

2. Name of Operator

**BURLINGTON
RESOURCES**

OIL & GAS COMPANY

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

1120' FNL, 1550' FWL, Sec. 25, T-30-N, R-11-W, NMPM

5. Lease Number

SF-079962

6. If Indian, All. or

Tribe Name

7. Unit Agreement Name

8. Well Name & Number

Payne #8

9. API Well No.

30-045-26643

10. Field and Pool

Blanco Mesaverde

11. County and State

San Juan Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

☐ Notice of Intent☐ Abandonment☐ Change of Plans☒ Subsequent Report☐ Recompletion☐ New Construction☐ Final Abandonment☐ Plugging Back☐ Non-Routine Fracturing☐ Casing Repair☐ Water Shut off☐ Altering Casing☐ Conversion to Injection☒ Other - Pay add

13. Describe Proposed or Completed Operations

12-3-97 MIRU. ND WH. NU BOP. TOOH w/157 jts 2 3/8" tbgs. TIH w/4 1/2" csg scraper to 4256'. SDON.

12-4-97 Pump 300 gal 15% Hcl down csg. Flush w/20 bbl 2% Kcl wtr. TIH to 4760' w/csg scraper. TOOH. TIH, ran GR log. TOOH. TIH w/4 1/2" RBP, set @ 4760'. TIH w/4 1/2" pkr, set @ 4227'. Load hole w/2% Kcl wtr. PT RBP to 3000 psi/5 min OK. TOOH w/pkr. TIH w/RBP, set @ 4180'. Load hole w/2% Kcl wtr. PT RBP & csg to 3000 psi/5 min, OK. Release pkr, TOOH. SDON.

12-5-97 TIH, latch RBP @ 4180'. TOOH. TIH, spot 250 gal 15% Hcl @ 4703'. Displace w/16.6 bbl 2% Kcl wtr. TOOH. TIH, perf Menefee w/1 SPF @ 4367, 4386, 4393, 4403, 4426, 4432, 4455, 4487, 4506, 4520, 4546, 4615, 4624, 4631, 4639, 4643, 4648, 4687, 4692, 4698, 4703'. TIH w/4 1/2" pkr, set @ 4258'. SDON.

12-6-97 Acidize w/1500 gal 15% Hcl. TOOH w/pkr. TIH w/pkrs, set @ 4159' & 4227'. SDON.

12-7-97 Frac Menefee w/2642 bbl slk wtr, 65,000# 20/40 Brady sd. Attempt to release pkr @ 4159'. SDON.

12-8-97 TIH w/fishing tools. TOOH fishing tools. TIH, Blow well & CO. SDON.

Continued on back

14. I hereby certify that the foregoing is true and correct.

Signed

Title Regulatory Administrator Date 1/14/98

(This space for Federal or State Office use)

APPROVED BY _____ Title _____

APPROVED

Date

CONDITION OF APPROVAL, if any:

1998

FARMINGTON DISTRICT OFFICE

NMOCD

12-9-97 Blow well & CO. SDON.
 12-10-97 Blow well & CO. TOO H w/pkrs. TIH, blow well & CO. SDON.
 12-11-97 Blow well & CO. TOO H. TIH w/4 1/2" csg scraper to 4725'. TOO H. SDON.
 12-12-97 Blow well & CO. TIH w/isolation pkrs, set @ 4157 & 4225'. Set plug in "R" nipple. Load tbg. Pressure up on pkrs to 2500 psi. TIH to retrieve plug. SD for weekend.
 12-15-97 TIH w/7" pkr. PT pkr to 500 psi, failed. Reset pkr. PT pkr to 500 psi, OK. Refrac Menefee w/4026 bbl slk wtr, 129,700# 20/40 Brady sd. CO after frac. SDON.
 12-16-97 Blow well & CO. TOO H w/7" pkr. TIH w/retrieving tool to top of lnr @ 2600'. Blow well & CO. SDON.
 12-17-97 Blow well & CO. TOO H w/isolation pkrs. TIH w/retrieving tool, blow well & CO. SDON.
 12-18-97 Blow well & CO. SDON.
 12-19-97 Blow well & CO. SD for weekend.
 12-22/23-97 Blow well & CO.
 12-24-97 Blow well & CO. SD for holiday.
 12-26/28-97 Blow well & CO. SDON.
 12-29-97 Blow well & CO. TOO H. TIH, ran after frac log @ 4200-4703'. Blow well & CO.
 12-30-97 Blow well & CO. TOO H. TIH, ran perf efficiency log @ 4200-5081'. TOO H. TIH w/4 1/2" pkr & 148 jts 2 3/8" 4.7# J-55 EUE tbg, set pkr @ 4246'. SDON.
 12-31-97 Release pkr, reset @ 4238'. Landed tbg below pkr @ 4534'. ND BOP. NU WH. RD. Rig released.
 1-1-98 MIRU. ND WH. NU BOP. Blow well & CO. SD for holiday.
 1-3/4-98 Blow well & CO. SDON.
 1-5-98 (Verbal approval to squeeze from Wayne Townsend, BLM).
 1-6-98 TIH, release pkr. TOO H w/148 jts 2 3/8" tbg & pkr. TIH w/CIBP, set @ 4266'. Load hole w/wtr. Establish injection. SDON.
 1-7-98 TIH w/cmt retainer, set @ 4088'. Load tbg w/wtr. PT tbg to 2000 psi, OK. Establish injection. Pressure up on csg to 500 psi. Pump 130 sx Class "G" neat cmt. Displace w/10 bbl wtr. Reversed out 8 bbl cmt. Sqz 90 sx of cmt below cmt retainer. TOO H. WOC. SDON.
 1-8-98 TIH w/bit, tag TOC @ 4082'. Drill out cmt retainer. Drill cmt @ 4088-4230'. TOO H. SDON.
 1-9-98 Load hole w/wtr. Hole held column of wtr, PT OK. TIH, drill out CIBP. Push CIBP to PBTD @ 5288'. TOO H. TIH. SD for weekend.
 1-12-98 TIH to 5160'. Blow well & CO. Drill out rest of CIBP @ 5160'. Blow well & CO to PBTD @ 5288'. TOO H. SDON.
 1-13-98 TIH, blow well & CO. TOO H. TIH w/152 jts 2 3/8" 4.7# J-55 EUE tbg, landed @ 4895'. Blow well & CO. RD. Rig released.