submitted in lieu of Form 3160-5

## UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT



Sundry Not	tices and Reports	on Wells	99	AUG -4 Pil 1: 27
1. Type of Well GAS		i Talà	5070 Euven	Lease Number SF-078505N NM If Indian, All. or Tribe Name
2. Name of Operator  RESOURCES  OIL  3. Address & Phone No. of Operation PO Box 4289, Farmington, NA  4. Location of Well, Footage, S. 1660'FSL, 1794'FWL, Sec.23,	M 87499 (505) 326	0]] <u>[</u> [ 5-9700		Well Name & Number Seymour #10
12. CHECK APPROPRIATE BOX TO IN  Type of Submission  _X_ Notice of Intent  Subsequent Report  Final Abandonment  13. Describe Proposed or Comp  It is intended to install procedure and wellbore di	Type  Abandonment Recompletic Plugging Ba Casing Repa Altering Ca X_ Other - Pum  pleted Operations  L a pump in the su	e of Actions on ack asir asing ap Install	Change of Pla New Construct Non-Routine F Water Shut of Conversion to ation	ins ion Tracturing If Injection
(This space for Federal or State	Title Regulat	ory Admin	<u>istrator</u> Date	: 8/4/99

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

### Seymour #10 PUMPING UNIT INSTALLATION PROCEDURE 8/3/99

# Unit K, Section 23, T31N, R09W, San Juan County, New Mexico Aircare Lat. 36 52.87' Aircare Long. 107 45.13'

- 1. MIRU PULLING UNIT.
- 2. BLOW DOWN TBG. KILL WELL W/ WATER ONLY IF NECESSARY.
- 3. NDWH / NUBOP.
- 4. PU 1 10' PUP JT. OF 2-3/8" TBG. AND TIH W/ 2-3/8" TBG. STRING AND LAND TBG. @ 3207'. PURGE VALVE WILL BE ON BOTTOM W/ 2-3/8"x10' PUP JOINT(3197'-3207'), 2-3/8"x6' PUP JOINT(3191'-3197'), 2-3/8"x4' PERFORATED SUB(3187'-3191') AND 2-3/8" SN @ 3187'.
- 5. HANG TBG. IN DONUT. NDBOP / NUWH.
- 6. TIH W/ NEW TOP HOLD DOWN ROD PUMP (2"x1-1/4"x10'x14' RHAC-Z), 4' SECTION CUP TYPE PLUNGER. RUN THREE 1-1/4" SINKER BARS, 125 3/4" GRADE D SUCKER RODS (W/ SPRAY METAL COUPLINGS), A SET OF 3/4" PONY RODS (2', 4', 6', 8') TO SPACE OUT, ONE 1-1/4"x 22 3/4" PIN POLISHED ROD AND ONE 1/1/4"x1-1/2"x10' POLISHED ROD LINER.
- 7. SEAT THE DOWNHOLE PUMP, HANG HORSES HEAD ON, SPACE PUMP.
- 8. LOAD TBG., PRESSURE TEST.
- 9. START PUMPING UNIT, AND TEST OK (ADJUST SPACING IF NEEDED).
- 10. RDMO.

COMPLY WITH ALL FEDERAL, STATE AND LOCAL RULES AND REGULATIONS RELATING TO OIL AND GAS OPERATIONS.

Prepared: E.J. Giles Office: 326-9584

Home: 325-8164 Pager: 324-2636

Pump Vendor: Energy Pump & Supply – (505)564-2874

### Seymour 10 (Current) Basin Fruitland Coal

### Unit K , Section 23, T31N, R9W, San Juan County, New Mexico

