| (Formerly 9-331) | BUREA | MENT OF THE I | INTERIOR verse side) | TRIPLICATE | 5. LEASE DESIGNATION | Nø. 1004-0135 31/31, 1985 N AND SERIAL NO. |
|--|--|--|---|--|---|--|
| SUN | IDRY NOT | ICES AND REPO | ORTS ONFRENEN | | SF 078977 | EE OR TRIBE NAME |
| (Do not use this form for proposals to drill or to deepen or pits back of A line was Comprosit.) Use "APPLICATION FOR PERMIT—" for such proposals.) | | | | | N/A | |
| OIL GAS WELL | OTESE | | 87 JUN 19 AM 11: | 4 | 7. UNIT AGREEMENT N | AMB |
| 2. NAME OF OPERATOR | roleum Co | *** | FARMINGTON RESOURC | EAREA | 8. PARM OR LEASE NA | ¥8 |
| 3. ADDRESS OF OPERATOR | roteam co | rporacion | FARMINGTON, NEW MI | EXICO | Butte | |
| 370 17th St. Suite 1700 Denver, Colo. 80202 4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* | | | | | 1 R | |
| See also space 17 below.) At surface | | | | | 10. PIBLD AND POOL, OR WILDCAT | |
| 1790' FNL, 970' FWL (SENW) | | | | | Basin Dakota | |
| | | | | | SURVEY OR AREA | |
| 14. PERMIT NO. | | 16. BLEVATIONS (Show v | rhether DF, BT, GB, etc.) | | Sec. 19-T30N- | -RISW |
| 6. | | <u> </u> | | | San Juan | New Mexi |
| × | Check Ap | propriate Box To Ind | icate Nature of Notice, | Report, or C | Other Data | |
| TEST WATER SHUT-OF | | CLL OR ALTER CASING | - , | SUBSBQ0 | DENT REPORT OF: | |
| PRACTURE TREAT | | ULTIPLE COMPLETE | WATER SHUT- | · · | REPAIRING V | I |
| SHOOT OR ACIDIZE | AI | BANDON* | SECOTING OR | | ALTERING CA | |
| REPAIR WELL (Other) | c: | TANGE PLANS | (Other)] | Notice of | Spudding of multiple completion | <u> </u> |
| MIRU Fou | r Corners | Drilling Rig # | ace locations and measured a | ertinent dates, nd true vertica | | of starting any and sones perti- |
| MIRU Fou Drill to Cement w Plug down | r Corners 265'. RU /200 sxs (n at 9:15 | Drilling Rig # & run 6 jts 8 236Ft3) Class | 3. Spud 12 1/4" h 5/8" 24# K-55 ST8 "B" + 2% CaC12. (est blind & pipe r | nole at 3: | including estimated dated depths for all markers :00 PM 6/13/87. Set casing a | of starting any and sones perti- |
| MIRU Fou Drill to Cement w Plug down | r Corners 265'. RU /200 sxs (n at 9:15 | Drilling Rig # & run 6 jts 8 236Ft3) Class ' PM 6/13/87. To | 3. Spud 12 1/4" h 5/8" 24# K-55 ST8 | nole at 3: AC casing Circulated cams, casi | including estimated dated depths for all markers :00 PM 6/13/87. Set casing a | t 258' KB. face. anifold |

*See Instructions on Reverse Side