

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

RECEIVED  
BLM

Sundry Notices and Reports on Wells

97 OCT 20 AM 8:42  
070 FARMINGTON, NM

1. Type of Well  
GAS

2. Name of Operator  
**BURLINGTON RESOURCES**  
OIL & GAS COMPANY

3. Address & Phone No. of Operator  
PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M  
835'FSL, 1180'FEL, Sec.10, T-30-N, R-9-W, NMPM

5. Lease Number  
SF-078201A

6. If Indian, All. or Tribe Name

7. Unit Agreement Name

8. Well Name & Number  
Riddle Com #200

9. API Well No.  
30-045-26919

10. Field and Pool  
Basin Fruitland Coal

11. County and State  
San Juan Co, NM

RECEIVED  
OCT 27 1997

OIL CON. DIV.  
DIST. 3

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission	Type of Action	
<input type="checkbox"/> Notice of Intent	<input checked="" type="checkbox"/> Abandonment	<input type="checkbox"/> Change of Plans
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion	<input type="checkbox"/> New Construction
<input type="checkbox"/> Final Abandonment	<input type="checkbox"/> Plugging Back	<input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> Water Shut off
	<input type="checkbox"/> Altering Casing	<input type="checkbox"/> Conversion to Injection
	<input type="checkbox"/> Other -	

13. Describe Proposed or Completed Operations

9-15-97 MIRU. ND WH. NU BOP. TOOH w/89 jts 2 3/8" tbg. TIH w/7" cmt retainer to 2620'. Work retainer, unscrewed from setting tool & fell to top of 5 1/2" lnr. (Verbal approval to continue plugging from Wayne Townsend, BLM). TOOH. TIH open ended to 2620'. Plug #1: pump 50 sx Class "B" neat cmt @ 2450-2620'. TOOH to 2000'. WOC. SDON.

9-16-97 TIH, tag TOC @ 2496'. Load hole w/80 bbl wtr. PT csg to 500 psi, OK. Plug #2: pump 20 sx Class "B" neat cmt @ 2400-2496'. TOOH to 1803'. Plug #3: pump 58 sx Class "B" neat cmt inside csg @ 1500-1802'. TOOH to 290'. PT bradenhead to 300 psi, OK. Plug #4: pump 80 sx Class "B" neat cmt down csg & out csg valve. Circ 1 bbl cmt to surface. TOOH. WOC. ND BOP. Cut off WH. Install dry hole marker w/15 sx Class "B" neat cmt. RD. Rig released. (Joe Sanchez, BLM on location for plugging). Well plugged and abandoned 9-16-97.

14. I hereby certify that the foregoing is true and correct.

Signed Duane W. Spencer Title Regulatory Administrator Date 10/13/97

(This space for Federal or State Office use)  
APPROVED BY /s/ Duane W. Spencer Title \_\_\_\_\_ Date OCT 20 1997  
CONDITION OF APPROVAL, if any: