UNITED STATES

DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

Sundry Notice:	s and Report	s on Well	ls				
1. Type of Well GAS			2007 - 1 4 - 1. 2 - 1 348 - 1 - 5 - 182	5.	Lease Number SF-081098 If Indian, All. or Tribe Name Unit Agreement Name		
2. Name of Operator		1	with 1 or 10.	: (3			
BURLINGTON RESOURCES OIL & G	AS COMPANY	921	CONL I			Jame & Nu	umber
3. Address & Phone No. of Operator PO Box 4289, Farmington, NM 8		26-9700		9.		#250 ell No. 5-26936	
4. Location of Well, Footage, Sec. 795'FNL 1040'FWL, Sec.3, T-30-N		M			Field Basin County	and Pool Fruitlan and Statian Co, 1	nd Coal ate
12. CHECK APPROPRIATE BOX TO INDIC	ATE NATURE O	F NOTICE	, REPORT,	OTHER	DATA		
Type of Submission _X_ Notice of Intent Subsequent Report Final Abandonment	Abandonme Recomplet Plugging Casing Re	ion _ Back _ pair _	tion Change New Con Non-Rou Water S Convers	struct tine E hut of	ion Fractur f		
13. Describe Proposed or Complet It is intended to install a attached procedure an	pump in the	subject	well accor	ding t	the 070 FATURACTON, NM	\sim	RECEIVED
14. I hereby certify that the for Signed had here (Child had here (Child approved by Child handle)	EJG) Title <u>F</u>		Administ	<u>crator</u>	_Date 3	3/2/99 TLW	

Riddle #250 PUMPING UNIT INSTALLATION PROCEDURE 2/12/99

Unit D, Section 3, T30N, R09W, San Juan County, New Mexico Aircare Lat. 36 50.72' Aircare Long. 107 46.38'

- 1. MIRU PULLING UNIT.
- 2. BLOW DOWN TBG. KILL WELL W/ WATER ONLY IF NECESSARY.
- 3. NDWH / NUBOP.
- 4. PU AT LEAST 2 JTS. OF TBG. TIH TO TAG FOR FILL.
- 5. TOH LAYING DOWN 2-7/8" TBG. (TBG. IS SET @ 2884', THERE ARE 94 JTS. OF 2-7/8" 6.5# J-55 WITH F NIPPLE @ 2852').
- 6. PU 4-3/4" BIT ON 2-3/8" TBG. AND TIH TO COTB, CIRC. HOLE CLEAN. TOH W/ SAME.
- 7. TIH W/ 2-3/8" TBG. STRING AND LAND TBG. @ 2910'. PURGE VALVE WILL BE ON BOTTOM W/ 2-3/8"x10' PUP JOINT(2900'-2910'), 2-3/8"x6' PUP JOINT(2894'-2900'), 2-3/8"x4' PERFORATED SUB(2890'-2894') AND 2-3/8" SN @ 2890'.
- 8. HANG TBG. IN DONUT. NDBOP / NUWH.
- 9. TIH W/ NEW TOP HOLD DOWN ROD PUMP (2"x1-1/4"x10'x14' RHAC-Z), 4' SECTION CUP TYPE PLUNGER. RUN THREE - 1-1/4" SINKER BARS, 113 - 3/4" GRADE D SUCKER RODS (W/ SPRAY METAL COUPLINGS), A SET OF 3/4" PONY RODS (2',4'.6',8') TO SPACE OUT, ONE - 1-1/4"x 22 - 3/4" PIN POLISHED ROD AND ONE - 1/1/4"x1-1/2"x10" POLISHED ROD LINER.
- 10. SEAT THE DOWNHOLE PUMP, HANG HORSES HEAD ON, SPACE PUMP.
- 11. LOAD TBG., PRESSURE TEST.
- 12. START PUMPING UNIT, AND TEST OK (ADJUST SPACING IF NEEDED).
- 13. RDMO.

COMPLY WITH ALL FEDERAL, STATE AND LOCAL RULES AND REGULATIONS RELATING TO OIL AND GAS OPERATIONS.

Prepared: E.J. Giles Office: 326-9584

Home: 325-8164 Pager: 324-2636 Bruce W. Bouge 2 16.99

Approved: Drilling/Supt.

Riddle #250

(Current)

Basin Fruitland Coal Unit D, Section 3, T30N, R9W, San Juan County, New Mexico

