

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR Tenneco Oil Company	8. FARM OR LEASE NAME Storey B LS
3. ADDRESS OF OPERATOR P.O. Box 3249 Englewood, CO 80155	9. WELL NO. 3A
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1175' 990' 1500' FNL, 1500' FWL	10. FIELD AND POOL, OR WILDCAT Blanco Mesaverde
14. PERMIT NO.	15. ELEVATIONS (Show whether SP, ST, OR, etc.) 5778 GL 5794
	12. COUNTY OR PARISH San Juan
	13. STATE NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON*

CHANGE PLANE

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

Spud & Drill

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS* (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Referenced well spud @ 12:45 a.m. on 8/26/88. Drilling procedure attached.

RECEIVED
SEP 23 1988
OIL CON. DIV
DIST. 3

18. I hereby certify that the foregoing is true and correct

SIGNED

J. S. Chit

TITLE

Staff Administrative Analyst

DATE

9/12/88

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

SEP 21 1988

NMOC

See Instructions on Reverse Side

FARMINGTON, N.M.

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any Department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

WELL NAME: STOREY B LS #3A

PROCEDURE:

8/26/88 WELL SPUD @ 12:45 AM 8-26-88. NOTIFIED K. TOWNSEND (BLM) @ 8:00 AM, SAME DAY.
DRILL TO 270'. SET AND CEMENT 9 5/8" CASING @ 263' W/ 230 CU FT CEMENT. BUMP PLUG, CMT IN PLACE. GOOD CIRC
W/8 BBLs TO SFS. WOC, CUT OFF 9 5/8 CSG & WELD ON BRADENHEAD, TEST TO 1000 PSI FOR 30 MIN - OK.

8/27/88 DRILL TO 1823'.

8/28/88 DRILL TO 2650', CIRC @ 2650'. DRL & SVY TO 2122', REAM TITE HOLE. SHORT TRIP 10 STANDS, CIRC & COND. WOC.

8/29/88 CIRC FOR CMT. RUN DIL-SFL-GR FROM 2668' TO 263'; CNL-LD FROM 2668' TO 590'; ASM 2668'-263'; NGR 2668'-590'.

8/30/88 DRILL TO 3520'. CMTD 7" CSG @ 2675 W/581 CU FT CMT. BUMP PLUG TO 500 PSI - OK, CMT IN PLACE. GOOD CIRC.
ND BOPE, SET SLIPS W/48,000#, CUT OFF, NU BOPE, TEST BLIND RAMS & CHOKE MANIFOLD @ 1000 PSI FOR 30 MIN - OK.
WOC. DP CMT & FLOAT EQUIP TO 2675'. TEST CSG TO 1000 PSI 15 MIN - OK. UNLOAD HOLD W/NITRO & DRY UP SAME.
DRD W/GAS TO 3520'.

8/31/88 DRILL TO 4335'.

9/1/88 DRILL TO 5000'.

9/2/88 RUN DIL-SFL FROM 4969' TO 2679', AMS FROM 4969' TO 2679' & FDCNL FROM 4969' TO 2679'. RD STAGE IN HOLE,
REAM 4915'-5000', DRD 5', POOH, LD DP & DC. SET & CMTD 4 1/2 CSG @ 4996' W/391 CU FT CMT. HUNG LINER
@ 4993' W/TOP @ 2512' & FC LATCHDOWN @ 4948'.

9/3/88 REL RIG @ 9:00 AM 9-3-88. ND, FLANGE UP & SECURE WELL.