

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

RECEIVED
BLM MAIL ROOM
96 FEB 28 AM 11:53

070 FARMINGTON, NM

1. Type of Well
GAS

2. Name of Operator
MERIDIAN OIL

3. Address & Phone No. of Operator
PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M
1650' FNL, 1035' FEL, Sec. 13, T-30-N, R-9-W, NMPM

5. Lease Number
SF-077231
6. If Indian, All. or
Tribe Name
7. Unit Agreement Name
8. Well Name & Number
Shaw #250
9. API Well No.
30-045-27036
10. Field and Pool
Basin Fruitland Coal
11. County and State
San Juan Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission	Type of Action
<input type="checkbox"/> Notice of Intent	<input checked="" type="checkbox"/> Abandonment
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion
<input type="checkbox"/> Final Abandonment	<input type="checkbox"/> Plugging Back
	<input type="checkbox"/> Casing Repair
	<input type="checkbox"/> Altering Casing
	<input type="checkbox"/> Other -
	<input type="checkbox"/> Change of Plans
	<input type="checkbox"/> New Construction
	<input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Water Shut off
	<input type="checkbox"/> Conversion to Injection

13. Describe Proposed or Completed Operations

- 2-14-96 MIRU. SDON.
- 2-15-96 ND WH. NU BOP. TOO H w/85 jts 2 3/8" tbg. TIH w/4 1/2" cmt retainer, set @ 2347'. PT tbg to 1200 psi, OK. Load hole w/22 bbl wtr. PT csg to 500 psi/5 min, OK. Establish injection. Plug #1: pump 31 sx Class "B" cmt below cmt retainer into Fruitland Coal perfs, pump 43 sx Class "B" cmt above cmt retainer, TOC @ 2060' TOO H to 1667'. SDON.
- 2-16-96 TIH to 1667'. Load hole w/4 bbl wtr. Plug #2: pump 66 sx Class "B" cmt inside csg @ 1324-1667'. TOO H to 281'. Plug #3: pump 18 sx Class "B" cmt inside 7" csg @ 188-281'. TOO H. Perf 3 sqz holes @ 190'. Attempt to establish injection. (Verbal approval to change plans from Wayne Townsend, BLM). Plug #4: pump 24 sx Class "B" cmt outside 7" csg, pump 27 sx Class "B" cmt inside 7" csg. Displace to 50'. Perf 3 sqz holes @ 50'. Establish circ down csg & out bradenhead w/2 bbl wtr. Plug #5: pump 32 sx Class "B" cmt down 7" csg & out bradenhead. Circ 1 bbl cmt to surface. WOC. ND BOP. Cut off WH. Install dry hole marker w/10 sx Class "B" cmt. RD. Rig released. Well plugged and abandoned 2-16-96.

14. I hereby certify that the foregoing is true and correct.

Signed [Signature] Title Regulatory Administrator Date 2/22/96

(This space for Federal or State Office use)

APPROVED BY _____ Title _____ Date _____

CONDITION OF APPROVAL, if any:

RECEIVED
MAR - 1 1996

OIL CON. DIV.

NMOC