

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR Meridian Oil Inc.	8. FARM OR LEASE NAME Grambling C
3. ADDRESS OF OPERATOR Post Office Box 4289, Farmington, NM 87499	9. WELL NO. 202
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1630'N, 1495'E	10. FIELD AND POOL, OR WILDCAT Basin Fruitland Coal
11. SEC. T. R. M. OR BLM. AND SURVEY OR AREA Sec. 14, T-30-N, R-10-W N.M.P.M.	12. COUNTY OR PARISH 13. STATE San Juan NM
14. PERMIT NO.	15. ELEVATIONS (Show whether OF, BY, OR, etc.) 6403'GL

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF	_____	PULL OR ALTER CASING	_____
FRACTURE TREAT	_____	MULTIPLE COMPLETE	_____
SHOOT OR ACIDIZE	_____	ABANDON*	_____
REPAIR WELL	_____	CHANGE PLANS	_____
(Other)	_____		_____

SUBSEQUENT REPORT OF:

WATER SHUT-OFF	_____	REPAIRING WELL	_____
FRACTURE TREATMENT	_____	ALTERING CASING	_____
SHOOTING OR ACIDIZING	_____	ABANDONMENT*	_____
(Other)	_____	Running Casing	_____

(NOTE: Report results of multiple completion on Well Completion or Recumpletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS. Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.*

09-19-88 TD 3048'. Ran 5 jts. 4 1/2", 10.5#, K-55 casing liner, 361' set @ 3048'. Float shoe set @ 3048'. Top of liner hanger @ 2854'. Cemented w/20 sks. Class "G" 65/35 Poz with 6% gel, 2% calcium chloride and 1/2 cu.ft./sx perlite (39 cu.ft.), followed by 75 sx Class "G" neat w/2% calcium chloride (86 cu.ft.) reversed to surface.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Regulatory Affairs

DATE

01-04-89

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side