	DEPARTMENT OF THE INTERIOR (Other Instructions on re- play 9-331) BUREAU OF LAND MANAGEMENT		Form approved. Budget Bureau No. 1004-0135 Expires August 31. 1985 5. LEASE DESIGNATION AND SERIAL NO. NM-03195 6. IF INDIAN, ALLOTTES OR TRISE NAME
SUNDRY (Do not use this form Use	Y NOTICES AND REPORTS C for proposals to drill or to deepen or plug by "APPLICATION FOR PERMIT—" for such pr	ON WELLS ack to a different reservoir. oppossis.)	
OIL GAS X OTHER			7. UNIT AGREEMENT NAME
WELL WELL WELL WELL A OTHER 2. NAME OF OPERATOR			8. PARM OR LEASE NAME
Meridian Oil Inc.			Sunray J
Post Office Box 4289, Farmington, NM 87499			210
The second secon			10. FIELD AND POOL, OR WILDCAT
4. Location of well (Report location clearly and in accordance with any State requirements.) See also space 17 below; At surface 790 'S, 880 W			Undes.Fruitland Coal 11. SEC. T. R. M. OR BLE. AND SURVEY OF ASSA Sec. 07, T-30-N, R-10-W N.M.P.M.
14. PERMIT NO.	SERNIT NO. 15. SLEVATIONS (Show whether DF, ET, GR, etc.) 6128 GL		12. COUNTY OR PARISH 13. STATE
			San Juan NM
	heck Appropriate Box To Indicate N		Miner Uara TENT REPORT OF:
	PULL OR ALTER CASING	WATER SHUT-OFF	REPAIRING WELL
TEST WATER SHUT-OFF FRACTURE TREAT	MULTIPLE COMPLETE	FRACTURE TREATMENT	ALTERING CASING
SHOOT OR ACIDIZE	ABANDON®	SECOTING OR ACIDIZING	ABANDONMENT*
REPAIR WELL (Other)	CHANGE PLANS	Note: Report results	of multiple completion on Well
(Other) Completion or Recompletion Report and Log form.) 17. DESCRIBE Engineers or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers—and somes pertinent to this work.)			
09-26-88 Spudded well at 5:15 pm 09-26-88. Dr jts. 9 5/8", 36.0#, K-55 surface casin Cemented with 200 sks. Class "B" with 3% calcium chloride (230 cu.ft.). circ WOC 12 hrs. Tested 600#/30 minutes, h			g set at 231'. 1/4#/sk. gel-flake and ulated to surface.
2: 16 2: 16 RC: AREA REXIGO	TD 2687'. Ran 63 jts. 7", 20.0#, K-55 intermediate casing, 2675' set @ 2687'. Cemented with 370 sks. Class "B" 65/35 Poz, with 6% gel, 2% calcium chloride and 1/2 cu.ft./sack perlite (714 cu.ft.) followed by 100 sks. Class "B" with 2% calcium chloride (115 cu.ft.). WOC 12 hours. Held 1200#/30		
SECTIVED SECTIVED SECTIVED SOUTH -3 PH 2: FARMINGTON, NEW MED	OIL		CENT I
			COM. DIV Dist. 3
18. I bereby certify that the f	Toregoing is true and correct Madfulf TITLE Re	gulatory Affairs	

MMOCC

DATE

*See Instructions on Reverse Side

TITLE _

(This space for Federal or State office use)

APPROVED BY CONDITIONS OF APPROVAL, IF ANY: