## UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

	es and Reports on-We	##D	
		5.	Lease Number SF-0 <del>8109</del> 8 0783/9
1. Type of Well	D	EOFINE	If Indian, All. or
GAS			Tribe Name
2. Name of Operator	<u></u>	_ • G.M. ∤ U. 185 <b>3</b> . 1 Transport	Unit Agreement Name
BURLINGTON RESOURCES OIL &	GAS COMPANY		<i>i</i> O
2 Address t Phone No. of Openator		_ 8.	Well Name & Number
3. Address & Phone No. of Operator PO Box 4289, Farmington, NM 87499 (505) 326-9700		9.	Riddle E Com #250 API Well No. 30-045-27103
4. Location of Well, Footage, Sec., T, R, M		10.	Field and Pool
1740'FSL 1035'FEL, Sec.4, T-30-	-N, R-9-W, NMPM	11.	Basin Fruitland Coa County and State San Juan Co, NM
12. CHECK APPROPRIATE BOX TO INDIC			DATA
Type of Submission X Notice of Intent	<b>Type of A</b> Abandonment	ction Change of Pl	ans
	Recompletion	New Construc	
Subsequent Report	Plugging Back	Non-Routine	
Final Abandonment	Casing Repair Altering Casing	Water Shut o	
	X Other -	Conversion C	J IIIJection
13. Describe Proposed or Complet	ed Operations		
It is intended to install a attached procedure a			to the
			97
			70 = =
			- 第 第 名
			14 PE
			-t Pi
			CELVETS -4 PH 2
			OEIVES 51.4 PH 2: 3
			OEIVES 5LM -4 PH 2: 33
14. I hereby certify that the fo	pregoing is true and	. correct.	CEIVES -4 PH 2: 33
The Street and	pregoing is true and (EJG) Title <u>Regulato</u>		
(This space for Federal or State (	(EJG) Title <u>Requlato</u>	ry Administrator	
Signed Stankered	(EJG) Title <u>Requlato</u>	ry Administrator	

Peggy

## Riddle E Com #250 PUMPING UNIT INSTALLATION PROCEDURE 2/12/99

## Unit I, Section 4, T30N, R09W, San Juan County, New Mexico Aircare Lat. 36 50.26' Aircare Long. 107 46.81'

- 1. MIRU PULLING UNIT.
- 2. BLOW DOWN TBG. KILL WELL W/ WATER ONLY IF NECESSARY.
- 3. NDWH / NUBOP.
- 4. PU 1 JT. OF TBG. TIH TO TAG FOR FILL.
- 5. TOH STANDING BACK 2-3/8" TBG. (TBG. IS SET @ 2857', THERE ARE 88 JTS. OF 2-3/8" 4.7# J-55 WITH F NIPPLE @ 2824').
- 6. PU 4-3/4" BIT ON 2-3/8" TBG. AND TIH TO COTB, CIRC. HOLE CLEAN. TOH W/ SAME.
- 7. TIH W/ 2-3/8" TBG. STRING AND LAND TBG. @ 2859'. PURGE VALVE WILL BE ON BOTTOM W/ 2-3/8"x10' PUP JOINT(2849'-2859'), 2-3/8"x6' PUP JOINT(2843'-2849'), 2-3/8"x4' PERFORATED SUB(2839'-2843') AND 2-3/8" SN @ 2839'.
- 8. HANG TBG. IN DONUT. NDBOP / NUWH.
- 9. TIH W/ NEW TOP HOLD DOWN ROD PUMP (2"x1-1/4"x10'x14' RHAC-Z), 4' SECTION CUP TYPE PLUNGER. RUN THREE 1-1/4" SINKER BARS, 111 3/4" GRADE D SUCKER RODS (W/ SPRAY METAL COUPLINGS), A SET OF 3/4" PONY RODS (2',4'.6',8') TO SPACE OUT, ONE 1-1/4"x 22 3/4" PIN POLISHED ROD AND ONE 1/1/4"x1-1/2"x10' POLISHED ROD LINER.
- 10. SEAT THE DOWNHOLE PUMP, HANG HORSES HEAD ON, SPACE PUMP.
- 11. LOAD TBG., PRESSURE TEST.
- 12. START PUMPING UNIT, AND TEST OK (ADJUST SPACING IF NEEDED).
- 13. RDMO.

COMPLY WITH ALL FEDERAL, STATE AND LOCAL RULES AND REGULATIONS RELATING TO OIL AND GAS OPERATIONS.

Prepared: E.J. Giles Office: 326-9584

Home: 325-8164 Pager: 324-2636 Approved Drilling Supt

## Riddle E Com #250 (Current) Basin Fruitland Coal Unit I, Section 4, T30N, R9W, San Juan County, New Mexico

