

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

RECEIVED
JAN 03 1990
OIL CON. DIV.
DIST. 3

WELL API NO.

30-045-27257

5. Indicate Type of Lease

STATE ☒

FEE ☐

6. State Oil & Gas Lease No.

B-11125

7. Lease Name or Unit Agreement Name

Northeast Blanco Unit

8. Well No.

450

9. Pool name or Wildcat

Basin Fruitland Coal

SUNDRY NOTICES AND REPORTS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT TO DRILL" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL WELL ☐

GAS WELL ☒

OTHER

2. Name of Operator

Blackwood & Nichols Co., Ltd.

3. Address of Operator

P. O. Box 1237, Durango, Colorado 81302

4. Well Location

Unit Letter N : 795 Feet From The South Line and 2010 Feet From The West Line

Section 32

Township 31N

Range 7W

NMPM

San Juan

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

6349' GL

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☒

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☒

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- 12-09-89 Spud 12-1/4" surface hole at 5:30 a.m., 12-08-89. Drill to 319'. Run 7 jts (304.32') 9-5/8" 36# J-55 casing, set at 317'; insert float at 277'. Cement with 250 sx (295 cf) Class B neat + 2% CaCl₂ + 1/4 #/sk cellophane flake. Circulate 17 Bbls cement. Plug down at 2:07 a.m.
- 12-10-89 Test BOP and 9-5/8" casing to 600 psi for 30 minutes - held OK. (CN)
- 12-12-89 TD hole at 2926'. Run 68 jts (2911.25') 7" 23# K-55 casing, set at 2923'; insert float at 2878'. Cement with 415 sx (697 cf) Class B 65/35 + 6% gel + .6% Halid 9 + 1/4 #/sk flocele. Tail in with 125 sx (147.5 cf) Class B neat + 1/4 #/sk flocele. Good circulation throughout. Circulate 36 Bbls cement. Plug down at 4:59 p.m., 12-11-89.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

William F. Clark

TITLE Operations Manager

DATE

2 Jan 90

TYPE OR PRINT NAME

William F. Clark

TELEPHONE NO.

(This space for State Use)

Original Signed by FRANK T. CHAVEZ

SUPERVISOR DISTRICT # 1

APPROVED BY

TITLE

DATE

JAN 03 1990

CONDITIONS OF APPROVAL, IF ANY: