

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE\*  
(Other instructions on re-  
verse side)

Form approved.  
Budget Bureau No. 1004-0135  
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON ~~WELLS~~ **MAIL ROOM**

(Do not use this form for proposals to drill or to deepen or plug back to a different depth.  
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER ☐ 89 DEC 27 AM 9:21

2. NAME OF OPERATOR Amoco Production Company ATTN: J. L. HAMPTON

3. ADDRESS OF OPERATOR P. O. Box 800 Denver, Colorado 80201

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface  
1140' FSL, 1700' FWL SE/SW

14. PERMIT NO. API 30 04527351

15. ELEVATIONS (Show whether DF, ST, GR, etc.) 6407 KB

5. LEASE DESIGNATION AND SERIAL NO. SF 078387-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME Kernaghan B

9. WELL NO. 8

10. FIELD AND POOL, OR WILDCAT Basin Fruitland Coal Gas

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec 33-T31N-R8W

12. COUNTY OR PARISH 13. STATE San Juan nm.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐  
☐  
☐  
☐

PULL OR ALTER CASING

☐  
☐  
☐  
☐

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON\*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☐  
☐  
☐  
☐

REPAIRING WELL

☐  
☐  
☐  
☒

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT\*

(Other) Spud & set casing  
(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Spud a 12 1/4" surface hole on 6/2/89 at 1400 hrs. Drilled to 277'.  
Set 9 5/8" 36# J55 surface casing at 277'. Cemented with 3005x CB.  
Pressure tested casing to 1500 psi. Drilled a 8 3/4" hole to a TD of 3052' on 6/5/89. Set 7" 23# K55 production casing at 3052'. Cemented with 534 5x lite, tail w/100 5x neat CB. Circulated 23 BBLs good cement to the surface.

Rig Released at 1930 hrs. on 6/5/89.

RECEIVED  
FEB 07 1990  
OIL CON. DIV.  
DIST. 3

18. I hereby certify that the foregoing is true and correct

SIGNED

J. L. Hampton/CB

TITLE Sr. Staff Admin. Supv.

DATE

12/21/89

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

\*See Instructions on Reverse Side