TNovember 1983; (Formerly 9-331)	UNITED STATES DEPARTMENT OF THE INTER BUREAU OF LAND MANAGEMEN		5. LEASE DESIGNATION IND SERIAL S SF 079043
SUN (Do not use this	DRY NOTICES AND REPORTS (form for proposals to drill or to deepen or plur Use "APPLICATION FOR PERMIT—" for such p	ON WELLS back to a different reservoir.	8. IF INDIAN, ALLOTTEE OR TRIBE NAME
1.			7. UNIT AGREEMENT NAME
OIL GAS WELL	X OTHER		Northeast Blanco Unit
2. NAME OF OPERATOR		i e e	8. PARM OR LEASE NAME
	Blackwood & Nichols Co., Ltd.		Northeast Blanco Unit
3. ADDRESS OF OPERATOR	D 0 D 1227 D 0.1.	. 1 . 01202	9. WELL NO. 454
	P. O. Box 1237, Durango, Color port location clearly and in accordance with any		10. FIELD AND POOL, OR WILDCAT
See also space 17 belo At surface	w.)	DECENT	Basin Fruitland Coal
	101 777		11. SRC., T., E., M., OE BLE. AND SURVEY OR ARMA
1010' FNL, 13	10' FEL	JANCET	Sec. 33, T31N, R7W
14. PERMIT NO.	15. ELEVATIONS (Show whether of	RTAR Stales	12. COUNTY OR PARISH 13. STATE
30-045-27402	6548' Gl.	Oil Constant	San Juan New Mexico
16.	Check Appropriate Box "o Indicate N	lature of Notice, Report, or O	ther Data
N	OTICE OF INTENTION TO:		ENT REPORT OF:
TEST WATER SHUT-OF	PULL OR ALTER CASING	WATER SHUT-OFF	REPAIRING WELL
PRACTURE TREAT	MULTIPLE COMPLETS	FRACTURE TREATMENT	ALTERING CASING
SHOOT OR ACIDIZE	ABANDON*	SECOTING OR ACIDIZING	*THE WOODKABA
REPAIR WELL	CHANGE PLANS	(Other) <u>Cementing</u>	
(Other)		(Norm: Report results of	of multiple completion on Well tion Report and Log form.)
nent to this work.)* 10-25-89	COMPLETED OPERATIONS (Clearly State all pertinent well is directionally drilled, give subsurface located by the subsurface has been brilled to 168.	le at 12:00 midnig	ht, 10-25-89
10-26-89	Drill to 320'. Run 8 jts (321.62') new 9-5/8" 36# USS ST&C casing. Land casing at 332' KB. Pump 20 Bbls water. Pump 250 sx (295 cf) Class B with 2% CaCl ₂ + 1/4 #/sk celloflake. Drop plug and displace plug to 297' with 23 Bbls water. Displacement pressure 225 psi. Circulate 20 Bkls cement. Plug down at 12:45 p.m., 10-25-89.		
10-27-89	Pressure tested 9-5/8" casing to 600 psig for 30 minutes - held OK.		
10-29-89	Drilled to TD at 3126'. Ran 74 jts (3110.96') new 7" 23# J-55 casing. Shoe at 3125'; float at 3080'.		
	Pump 20 Bbls mud flush. Cement with 460 sx (764 cf) Halliburton Lite + 6% gel + .6% Halid 322 + 1/4 #/sk flocele. Tailed in with 125 sx (148 cf) Class B + 1/4 #/sk Flocele. Circulated 35 Bbls cement. Plug down at 7:05 a.m., 10-29-89.		
18. I hereby certify that t	he foregoing is true and correct		11/2- '00
SIGNED William	F. Clark TITLE OF	erations Manager	DATE 11 De 89
(This space for Federa	i or State office use)	Ar	CEPTED FOR RECORD
APPROVED BY	TITLE	Ru	ULI ALTE I UN ILLUUIS
CONDITIONS OF APP	ROVAL, IF ANT:		JAN 0 4 1990
	#C 14	on Reverse Side	

FARMING FOR RESUDENCE AREA