

Submit to Appropriate
District Office
State Lease - 6 copies
Fee Lease - 5 copies
DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Benito Rd., Aztec, NM 87410

State of New Mexico
Energy, Minerals and Natural Resources Department

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

Form C-105
Revised 1-1-89

WELL API NO.	30-045-27452
5. Indicate Type of Lease	STATE ☒ FEE ☐
6. State Oil & Gas Lease No.	B-10938-36

7. Lease Name or Unit Agreement Name	EPNG Com
--------------------------------------	----------

8. Well No.	1R
9. Pool name or Wildcat	Blanco Mesa Verde

WELL COMPLETION OR RECOMPLETION REPORT AND LOG				
1a. Type of Well: OIL WELL ☐ GAS WELL ☒ DRY ☐ OTHER ☐				
b. Type of Completion: NEW WELL ☒ WORK OVER ☐ DEEPEN ☐ FLUG BACK ☐ DEEP REPAIR ☐ OTHER ☐				
2. Name of Operator Meridian Oil Inc.				
3. Address of Operator PO Box 4289, Farmington, NM 87499				
4. Well Location Unit Letter B : 790 Feet From The North Line and 1450 Feet From The East Line Section 32 Township 30N Range 8W NMPM San Juan County				
10. Date Spudded 09-29-39	11. Date T.D. Reached 10-07-89	12. Date Compl. (Ready to Prod.) 10-19-89	13. Elevations (DF & REB, RT, GR, etc.) 6113' GL	14. Elev. Casinghead
15. Total Depth 5542'	16. Plug Back T.D.	17. If Multiple Compl. How Many Zones?	18. Intervals Drilled By Rotary Tools yes	Cable Tools
19. Producing Interval(s), of this completion - Top, Bottom, Name Mesa Verde - 4418-5388'				20. Was Directional Survey Made no
21. Type Electric and Other Logs Run 2 Logs				22. Was Well Cored no

23. CASING RECORD (Report all strings set in well)					
CASING SIZE	WEIGHT LB/FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
9 5/8"	40.0#	408'	12 1/4"	354 cu. ft.	
7"	23.0#	3205'	8 3/4"	932 cu. ft.	
4 1/2"	10.5#	5536'	6 1/4"	440 cu. ft.	

24. LINER RECORD				25. TUBING RECORD			
SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN	SIZE	DEPTH SET	PACKER SET
					2 3/8"	5262'	

26. Perforation record (interval, size, and number)		27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.	
4418-22', 4437-40', 4445-52', 4474-79', 4484-38', 4534-40', 4548-58', 4562-74', 4583-90', 4604-10', 4614-18', 4680-35', 4703-08', 4740-56', 4826-30', 4834-44', cont'd on back		DEPTH INTERVAL 4418-5388'	
		AMOUNT AND KIND MATERIAL USED 396,400# sand; 372.688 gal. fluid	

28. PRODUCTION							
Date First Production 10-13-39		Production Method (Flowing, gas lift, pumping - Size and type pump) flowing-capable of comm. hydrocarbon prod.				Well Status (Prod. or Shut-in) shut in	
Date of Test 10-31-39	Hours Tested 3 hrs	Choke Size 3/4"	Prod'n For Test Period	Oil - Bbl	Gas - MCF	Water - Bbl	Gas - Oil Ratio
Flow Tubing Press. 165	Casing Pressure 556	Calculated 24-Hour Rate	Oil - Bbl	Gas - MCF 2375	Water - Bbl	Oil Gravity - API - (Corr.)	

29. Disposition of Gas (Sold, used for fuel, vented, etc.) to be sold	Test Witnessed By: Joel Lee
--	--------------------------------

30. List Attachments - none

31. I hereby certify that the information shown on both sides of this form is true and complete to the best of my knowledge and belief

Signature Peggy Bradfield Printed Name Peggy Bradfield Title Reg. Affairs Date 1-10-90

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 25 through 29 shall be reported for each zone. The form is to be filed in triplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy _____	T. Canyon _____	T. Ojo Alamo 1790	T. Penn. "B" _____
T. Salt _____	T. Strawn _____	T. Kirtland-Fruitland 1833/2370	T. Penn. "C" _____
B. Salt _____	T. Atoka _____	T. Picured Cliffs 2810	T. Penn. "D" _____
T. Yates _____	T. Miss _____	T. Cliff House 4330	T. Leadville _____
T. 7 Rivers _____	T. Devonian _____	T. Menefee 4618	T. Madison _____
T. Queen _____	T. Silurian _____	T. Point Lookout 5021	T. Elbert _____
T. Grayburg _____	T. Monroya _____	T. Mancos _____	T. McCracken _____
T. San Andres _____	T. Simpson _____	T. Gallup _____	T. Ignacio Otzte _____
T. Glorieta _____	T. McKee _____	Base Greenhorn _____	T. Granite _____
T. Paddock _____	T. Ellenburger _____	T. Dakota _____	T. _____
T. Blinbry _____	T. Gr. Wash _____	T. Morrison _____	T. _____
T. Tubb _____	T. Delaware Sand _____	T. Todilto _____	T. _____
T. Drinkard _____	T. Bone Springs _____	T. Entrada _____	T. _____
T. Abo _____	T. _____	T. Wingate _____	T. _____
T. Wolfcamp _____	T. _____	T. Chinle _____	T. _____
T. Penn _____	T. _____	T. Permian _____	T. _____
T. Cisco (Bough C) _____	T. _____	T. Penn "A" _____	T. _____

OIL OR GAS SANDS OR ZONES

No. 1, from _____ to _____
 No. 2, from _____ to _____
 No. 3, from _____ to _____
 No. 4, from _____ to _____

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from _____ to _____ feet
 No. 2, from _____ to _____ feet
 No. 3, from _____ to _____ feet

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology	From	To	Thickness in Feet	Lithology
1790	1833	43	White, cr-gr ss.	4330	4618	288	Light gry, med-fine gr
1833	2370	437	Gry sh interbedded w/ tight, gry, fine-gr ss	4618	5021	403	ss, carb sh & coal
2370	2810	440	Dk gry-gry carb sh, coal, grn silts, light-med gry, tight, fine-gr ss.	5021	TD		Med-dark gry, fine-gr ss, carb sh & coal
2810	3610	600	Brn-gry, fine-gr, tight, ss.				Med-light, med-gry very fine gr ss w/ frequent sh breaks in lower part of formatic
3610	4330	720	Light gry, med-fine gr, ss., carb sh & coal				
Perf's cont'd. 4870-76', 4934-41', 4950-60', 4984-96'; 5022-40', 5044-50', 5054-58', 5078-88', 5108-20', 5128-38', 5146-54', 5162-70', 5226-36', 5272-84', 5356-63', 5368-72', 5382-88'							