

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED
BLM

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.

SUBMIT IN TRIPLICATE

1. Type of Well
☐ Oil Well ☐ Gas Well ☐ Other Salt Water Disposal Well

2. Name of Operator
Amoco Production Company ATTN: J.L. HAMPTON

3. Address and Telephone No.
P. O. Box 800 Denver, Colorado 80201

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)
1270' FNL, 580' FWL NW/NW Sec. 26, T30N, R9W

5. Lease Designation and Serial No.
SF-078139

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.
E. E. Elliott SWD 1

9. API Well No.
30-045-27799

10. Field and Pool, or Exploratory Area
WC Morrison/Bluff/Entrada

11. County or Parish, State
San Juan, New Mexico

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
- ☒ Subsequent Report
- ☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
- ☐ Recompletion
- ☐ Plugging Back
- ☐ Casing Repair
- ☐ Altering Casing
- ☒ Other Spud Report

- ☐ Change of Plans
- ☐ New Construction
- ☐ Non-Routine Fracturing
- ☐ Water Shut-Off
- ☐ Conversion to Injection
- ☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Please see the attached spud report associated with the subject well.

Please contact Cindy Burton (303) 830-5119 if you have any question.

ACCEPTED FOR RECORD

OCT 22 1991

FARMINGTON RESOURCE AREA

3Y

14. I hereby certify that the foregoing is true and correct

Signed J.L. Hampton Title Sr. Staff Admin. Supervisor

Date 10/14/91

(This space for Federal or State office use)

Approved by _____
Conditions of approval, if any: _____

Title _____ Date _____

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side

E.E.ELLIOTT SWD

9/1/90 RAN 30" CONDUCTOR. SET AT 32'. CEMENT TO SURFACE

SPUD WELL 9/2/90 AT 10:00 A.M. DRILLED TO 530'. RAN 20" 94# K55 BT&C SURFACE CASING TO 527'. CEMENTED WITH 655 SX CLASS G W/2% CACL2. TAIL WITH 251 SX CLASS G NEAT CEMENT. CIRCULATED 18 BBLS TO SURFACE. TESTED CASING TO 800 PSI, HELD.

DRILLED A 17.5" HOLE TO 3000' ON 9/14/90. RAN 13 3/8" 61#,68#, AND 54.5# K55 ST&C CASING TO 2999'. DV TOOL SET AT 1755'. CEMENTED 1ST STAGE WITH 550 SX 65/35 POZ NEAT, TAIL WITH 1300 SX CLASS G. CIRCULATED 60 BBLS CEMENT AND 85 BBLS MUD TO SURFACE. 2ND STAGE CEMENTED WITH 1775 SX 65/35 CLASS G NEAT, TAIL WITH 175 SX CLASS G. CIRCULATED 100 BBLS TO SURFACE.

DRILLED A 12 1/4" HOLE TO 5431' ON 9/23/90. RAN 9 5/8" 43.5#, 36.4# N80 ,K55 LT&C CASING TO 5427'. DV TOOL SET AT 2633'. CEMENTED 1ST STAGE WITH 1000 SX CLASS G 50/50 POZ, TAIL WITH 100 SX CLASS G. CIRCULATED 75 BBLS CEMENT TO SURFACE. CEMENTED 2ND STAGE WITH 650 SX CLASS G 65/35 LITE POZ, TAIL WITH 100 SX CLASS G. CIRCULATED 10 BBLS CEMENT TO SURFACE. TESTED CSG TO 2000 PIS. HELD.

DRILLED A 8 1/2" HOLE TO 8536' ON 10/23/90. RAN 7" 23#,26#, K55 LT&C CASING TO 8528'. DV TOOL SET AT 7338'. CEMENTED WITH 225 SX CLASS G. DV TOOL DID NOT OPEN; NO SECOND STAGE CEMENT PUMPED. RIG RELEASED 10/24/90.

SEE ADDITIONAL SUNDRY FOR SUBSEQUENT WORK..