Form 3160-5 (November 1983, (Formerly 9-331) BUREAU OF LAND MANAGEMENT SUBMIT IN TRIE (Other instruction PARTMENT OF THE INTERIOR verse side)	PLICATEO	Form approved. Budget Burcau No. 1004-0135 Expires August 31, 1985 5. LEASE DESIGNATION AND SERIAL NO SF-079004
SUN'DRY NOTICES AND REPORTS ON WELLS (Do not use the form for proposals to drill or to deepen or plug back to a different reserv Use "APPLICATION FOR PERMIT—" for such proposals.)	olr.	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
		7. UNIT AGREEMENT NAME
OIL CAS X OTHER		San Juan 32-8 Unit
2. HAME OF OPERATOR		S. FARM OR LEASE NAME
PHILLIPS PETROLEUM COMPANY		9. WELL NO.
300 W. Arrington, Suite 200, Farmington, NM 87401		224
4. Location of well (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface		10. FIELD AND POOL, OR WILDCAT Basin Fruitland Coal
Unit B, 800' FNL & 1657' FEL		11. SBC., T., R., M., OR BLE. AMD SURVEY OR AREA
	-	Sec. 10,
14. PERMIT NO. 15. BLEVATIONS (Show whether DF, RT, GR, etc.)		12. COUNTY OR PARISH 18. STATE
30-045-278671 6738' GL		San Juan NM
16. Check Appropriate Box To Indicate Nature of Notice, Rep	port, or O	her Data
NOTICE OF INTENTION TO:	-	NT ABPORT OF:
		[
TEST WATER SHUT-OFF PULL OR ALTER CASING WATER SHUT-OFF PRACTURE TREAT MULTIPLE COMPLETE PRACTURE TREATM		REPAIRING WELL
PRACTURE TREAT MULTIPLE COMPLETE PRACTURE TREAT RHOOT OR ACIDIZE ABANDON® SHOOTING OR ACID		ALTERING CASING
REPAIR WELL CHANGE PLANE (Other)	. Oper.	
(Note: Rep	ort results o	of multiple completion on Well tion Report and Log form.)
proposed work. If well is directionally drilled, give subsurface locations and measured and in nent to this work.)* 7-5-90 MIRU Aztec Well Service Rig No. 289. Spudded 12-1 hole @ 10:45 A.M. Ran 9-5/8",36#,J-55 ST&C Casing set @284', RU Dowell & Cement w/250 SX Cl "G" w/3% CaCl & 1#gelflake/Circ 104 SX cement. Plug down @9:45 P.M. Bumped plug w/300 NU BOP & tested to 600 Psi-Okay.	/sk	SEP1 1 1990
7-9-90 Ran 7", 23#,J-55, LT&C Casing set @3367', RU Dowell and cement w/500 SX 65/35 POZ w/12% gel and ½ #/sk gelflake followed w/100 SX cl "G" cement with ½ #/sk gelflake followed w/50 SX cl "G" 1½% D-65 and ½ #/SK gelflake. Circ 104 SX cement, Plug down @11:30 A.M. Bumped plug w/1500 PSI. Float held. PU BOP and set slips w/65,000#. RD & Released rig @1	t	
8-4-90 Drake #27 ran 5½", 23#, Pll0 Liner set @3609' Top liner @ 3261' RU Basin Perforators & ran GR/CCL logs.		
18. I hereby certify that the foregoing is true and correct		_
SIGNED CULLIFICATION Drilling Superviso	r	8-21-90 DATE
R.A. Allred		(505) 599-3403
(This space for Federal or State office use)	Δι	CCEPTED FOR RECORD
APPROVED BY TITLE		DATE
CONDITIONS OF APPROVAL, IF ANY:		SEP 04 1990

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instructions on Reverse Side

FARMINGTON RESOURCE AREA
BY 27

ALPECT (C)