Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROYED						
Budget Bureau No. 1004-013:	5					
Expires: March 31, 1993						

	Expires:	March	31, 199	13
Lease	Designati	on and	Serial	No.

NM-012641 SUNDRY NOTICES AND REPORTS ON WELLS 6. If Indian, Allottee or Tribe Name Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals 7. If Unit or CA, Agreement Designation SUBMIT IN TRIPLICATE Blanco 1. Type of Well Well Well Other 8. Well Name and No. 2. Name of Operator 9. API Well No. PHILLIPS PETROLEUM COMPANY 3. Address and Telephone No. 30-045-27919 300 West Arrington Suite 200, Farmington, NM 87401 505/599-3400 10. Field and Pool, or Exploratory Area 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) Basin Fruitland Coal 11. County or Parish, State Unit A, 1016' FNL & 895' FEL San Juan, NM Sec. 35, T31N, R8W CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 12. TYPE OF ACTION TYPE OF SUBMISSION Change of Plans Notice of Intent Abandonment Recompletion **New Construction** Non-Routine Fracturing Subsequent Report Plugging Back Casing Repair Water Shut-Off Altering Casing Conversion to Injection Final Abandonment Notice Other As Per NTL-FRA-90-1 (Note: Report results of multiple comp Completion or Recompletion Report and Log form.) 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Description of cement job to fulfill requirements for protection of usable water zones including the Ojo Alamo Formation, as per NTL-FRA-90-1. Time Started: 1114 _ Time Completed: __1216 Casing Size 7" 23# J-55 New Casing Seat 3018 Ft. Hole Size 8-3/4" _**,** __2140 __**,** __2096 Turbo Centralizers at 2185 Spring Type Centralizers at 2997 2929 , Mud Flush 10 BBls, Spacer 10 Fresh Water. Lead Slurry 500 SX 65/35 POZ, 12% Gel, ##/SK Flocele, 11.7 ppg @ 2.3 ft 3/SX yield. 100 SX Cl"G", 4#/SK Flocele, 15.8 ppg @ 1.15 ft 3/SX yield. Mid Slurry 50 SX C1"G", 1.5% D-65/SK, 17.0 ppg @ .99 ft 3/SK yield. Tail Slurry Displaced Plug with 115 Bbls Fresh Water. 170 BbYs/Sacks Volume Cement Circulated PSI, Average Rate 6 BPM, Bumped Plug with Average Pressure 250 14. I hereby certify that the foregoing is true, and correct R. A. Allred 9-26-90 Tide Drilling Supervisor ACCEPTED FOR RECORD (This space for Federal or State office use) OCT 04 1990

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any latter, included a statements

or representations as to any matter within its jurisdiction