#### UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

Sundry Noti	ces and Reports on Wells	5	<u> </u>
1. Type of Well GAS	3년(1) 전 (1)	5.	Lease Number SF-078505 If Indian, All. or Tribe Name
2. Name of Operator		7. · · · · · · · · · · · · · · · · · · ·	Unit Agreement Name
RESOURCES OIL S	& GAS COMPANY	32. <b>3</b>	
3. Address & Phone No. of Operat	· Or	8.	Well Name & Number Seymour #718
PO Box 4289, Farmington, NM		9.	API Well No. 30-045-28092
4. Location of Well, Footage, Se 940'FNL 1815'FWL, Sec.14, T-3			Field and Pool Basin Fruitland Coal
		11.	County and State San Juan Co, NM
12. CHECK APPROPRIATE BOX TO IND	DICATE NATURE OF NOTICE,	REPORT, OTHER	DATA
Type of Submission	Type of Acti	ion	
_X_ Notice of Intent		Change of Plange New Construct	
Subsequent Report		Non-Routine E Water Shut of	
Final Abandonment	Altering Casing _X_ Other -		
13. Describe Proposed or Compl  It is intended to install	a pump in the subject we	ell according t	to the attached
procedure and wellh	bore diagram.		_ 0
			RECEIVED 9 MAR -4 PH 2 070 FACCULATION
	roregoing is true and co	rrect.	
14. I hereby certify that the			
<i>j</i> ' · <sup>-</sup>	(EJG) Title <u>Regulatory</u>	<u>Administrator</u>	_Date 3/2/99 TLW

## 43

### Seymour #718 PUMPING UNIT INSTALLATION PROCEDURE 2/25/99

### Unit B, Section 14, T31N, R09W, San Juan County, New Mexico Aircare Lat. 36 54.15' Aircare Long. 107 44.79'

- 1. MIRU PULLING UNIT.
- 2. BLOW DOWN TBG. KILL WELL W/ WATER ONLY IF NECESSARY.
- 3. NDWH / NUBOP.
- 4. PU AT LEAST 1 JT. OF TBG. TIH TO TAG FOR FILL.
- 5. TOH STANDING BACK 2-3/8" TBG. (TBG. IS SET @ 3273', THER): ARE 105 JTS. OF 2-3/8" 4.7# J-55 WITH F NIPPLE @ 3240').
- 6. PU 4-3/4" BIT ON 2-3/8" TBG. AND TIH TO COTB, CIRC. HOLE CLEAN. TOH W/ SAME.
- 7. TIH W/ 2-3/8" TBG. STRING AND LAND TBG. @ 3292'. PURGE VALVE WILL BE ON BOTTOM W/ 2-3/8"x10' PUP JOINT(3282'-3292'), 2-3/8"x6' PUP JOINT(3276'-3282'), 2-3/8"x4' PERFORATED SUB(3272'-3276') AND 2-3/8" SN @ 3272'.
- 8. HANG TBG. IN DONUT. NDBOP / NUWH.
- 9. TIH W/ NEW TOP HOLD DOWN ROD PUMP (2"x1-1/4"x10'x14' RHAC-Z), 4' SECTION CUP TYPE PLUNGER. RUN THREE 1-1/4" SINKER BARS, 128 3/4" GRADE D SUCKER RODS (W/ SPRAY METAL COUPLINGS), A SET OF 3/4" PONY RODS (2',4',6',8') TO SPACE OUT, ONE 1-1/4"x 22 3/4" PIN POLISHED ROD AND ONE 1/1/4"x1-1/2"x10' POLISHED ROD LINER.
- 10. SEAT THE DOWNHOLE PUMP, HANG HORSES HEAD ON, SPACE PUMP.
- 11. LOAD TBG., PRESSURE TEST.
- 12. START PUMPING UNIT, AND TEST OK (ADJUST SPACING IF NEEDED).
- 13. RDMO.

COMPLY WITH ALL FEDERAL. STATE AND LOCAL RULES AND REGULATIONS RELATING TO OIL AND GAS OPERATIONS.

Prepared: E.J. Giles

Office: 326-9584 Home: 325-8164 Pager: 324-2636 Bruce W. Doy 9, 3.1.99

Approved Drilling Sup

# Seymour #718 (Current) Basin Fruitland Coal Unit B, Section 14, T31N, R9W, San Juan County, New Mexico

