

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT - " for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Phillips Petroleum Company

3. Address and Telephone No.

5525 Highway 64, NBU 3004, Farmington, NM 87401

505-599-3454

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit G, 1790' FNL & 1093' FEL
Section 23, T31N, R8W

5. Lease Designation and Serial No.

SF-081089

6. Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

San Juan 32-8 Unit

8. Well Name and No.

SJ 32-8 Unit #237

9. API Well No.

30-045-28209

10. Field and Pool, or exploratory Area

Basin Fruitland Coal

11. County or Parish, State

San Juan, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Deepen & install PCP
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

6/3/98

MIRU Big A #38. Set tubing plugs and BPV. ND WH. NU BOPs. Unset tubing hanger. Latched onto Baker Lok-set Packer @ 3002'. COOH w/2-7/8" tubing. RIH w/4-1/2" mill on bit & workstring. Tagged TD @ 3357'. Drilled out casing shoe from 3357' to 3363'. COOH w/mill. GIH w/4-1/2" bit. CO fill. Drilled ahead from 3363' to 3376' with air & mist. COOH. 4-1/2" mill tooth bit left in hole. Fish @ 3376'.

GIH w/stator on 2-7/8" 6.5# J-55 production tubing. Installed BPVs in dual tubing hanger. Landed hanger in tubing head with E0 tubing @ 3369' and "F" nipple set @ 3361'. PCP Stator set @ 3348'. ND BOPs. NU WH. Removed BPVs. Installed 7/8" rods into stator. NU PCP drive head. Pumped off expendable check. RD & MO.

14. I hereby certify that the foregoing is true and correct

Signed

Title

Regulatory Assistant

(This space for Federal or State office use)

Approved by

Title

Conditions of approval, if any:

JUL 02 1998