UNITED STATES

DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

BUREAU O	F LAND MANAGEMENT	and the second	
Sundry Noti	ces and Reports on Wells		
1. Type of Well GAS	AUO 3 C	5. 1390 6. 1390 7. 110 B	Lease Number SF-078439 If Indian, All. or Tribe Name Unit Agreement Name
2. Name of Operator	100 mg	No Day	
RESOURCES OIL S	E GAS COMPANY	No O	مير
	was a second	8.	Well Name & Number Johnston Federal #29
3. Address & Phone No. of Operator PO Box 4289, Farmington, NM 87499 (505) 326-9700		9.	API Well No. 30-045-28210
4. Location of Well, Footage, Sec., T, R, M		10.	Field and Pool
1550'FSL, 1210'FWL, Sec.7, T-	11. County		Basin Fruitland Coal County and State San Juan Co, NM
Subsequent Report Final Abandonment 13. Describe Proposed or Compl It is intended to install procedure and wellbore dia	Casing Repair Altering Casing X Other - Pump Install Leted Operations a pump in the subject well	Lation	ff o Injection
			RECEIVED 99 AUG -4 PH 1: 3 070 Barray (2001) NB
14. I hereby certify that the Signed State Approved BY A TO State CONDITION OF APPROVAL, if any:	e Office use)	<u>nistrator</u> Dat	

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

<u>Johnston Federal #29</u> <u>PUMPING UNIT INSTALLATION PROCEDURE</u> <u>7/27/99</u>

Unit K, Section 7, T31N, R9W, San Juan County, New Mexico Aircare Lat. 36 45.94' Aircare Long. 107 25.21'

- 1. MIRU PULLING UNIT.
- 2. BLOW DOWN TBG. KILL WELL W/ WATER ONLY IF NECESSARY.
- 3. NDWH / NUBOP.
- 4. PU 1 JT. OF TBG. TIH TO TAG FOR FILL.
- 5. TOH STANDING BACK 2-3/8" TBG. (TBG. IS SET @ 3440', THERE ARE 111 JTS. OF 2-3/8" 4.7# J-55 WITH F-NIPPLE @ 3407').
- 6. PU 4-3/4" BIT ON 2-3/8" TBG. AND TIH TO COTB, CIRC. HOLE CLEAN. TOH W/ SAME.
- 7. TIH W/2-3/8" TBG. STRING AND LAND TBG. @ 3454'. PURGE VALVE WILL BE ON BOTTOM W/2-3/8"x10' PUP JOINT(3444'-3454'), 2-3/8"x6' PUP JOINT(3438'-3444'), 2-3/8"x4' PERFORATED SUB(3434'-3438') AND 2-3/8" SN @ 3434'.
- 8. HANG TBG. IN DONUT. NDBOP / NUWH.
- 9. TIH W/ NEW TOP HOLD DOWN ROD PUMP (2"x1-1/4"x10'x14' RHAC-Z), 4' SECTION CUP TYPE PLUNGER. RUN THREE 1-1/4" SINKER BARS, APPROX. 135 3/4" GRADE D SUCKER RODS (W/ SPRAY METAL COUPLINGS), A SET OF 3/4" PONY RODS (2' ,4' ,6' ,8') TO SPACE OUT, ONE 1-1/4"x 22 3/4" PIN POLISHED ROD AND ONE 1/1/4"x1-1/2"x10' POLISHED ROD LINER.
- 10. SEAT THE DOWNHOLE PUMP, HANG HORSES HEAD ON, SPACE PUMP.
- 11. LOAD TBG., PRESSURE TEST.
- 12. START PUMPING UNIT, AND TEST OK (ADJUST SPACING IF NEEDED).
- 13. RDMO.

COMPLY WITH ALL FEDERAL, STATE AND LOCAL RULES AND REGULATIONS RELATING TO OIL AND GAS OPERATIONS.

Prepared: E.J. Giles Office: 326-9584

Home: 325-8164 Pager: 324-2636 Pump Vendor is Energy Pump & Supply @ 564-2874.

Johnston Federal 29

Basin Fruitland Coal Unit K, Section 7, T31N, R9W, San Juan County, New Mexico (Current)

