

to appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.

5. Indicate Type of Lease

STATE ☒

FEE ☐

6. State Oil & Gas Lease No.

E 1193-3

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE APPLICATION FOR PERMIT
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL
WELL ☐

GAS
WELL ☒

OTHER

2. Name of Operator

MESA OPERATING LIMITED PARTNERSHIP

3. Address of Operator

P.O. BOX 2009, AMARILLO, TEXAS 79189

7. Lease Name or Unit Agreement Name

FC STATE COM

8. Well No.

26

9. Pool name or Wildcat

Basin Fruitland Coal

4. Well Location

Unit Letter K : 1535 Feet From The South Line and 2275 Feet From The West Line

Section 36 Township 30N Range 8W NMPM San Juan County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

6057' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: AMEND DRILLING PROGRAM ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

The Permit to Drill is amended to show the following open hole completion.

Propose to spud well with 12 1/4" hole and drill to 200' and set 9 5/8" surface casing. Will cement with 150 sx of Class "B" and raise cement to surface. Will nipple up 3000 psi BOP assembly and drill 8 3/4" hole to 2500' with fresh water mud system. Will set 7" casing at 2500' and cement with 350 sx Pozmix followed by 100 sx Class "B" cement. Will nipple up 3000 psi BOP/diverter assembly and drill 6" hole to 2820' with air and water. Will hang off 5" liner at 2475'-2820'.

xc. NMOCD-A (0+6), WF, Reg. Land, Expl., Drlg.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Carolyn L. McKee

TITLE Sr. Regulatory Analyst

DATE 9/13/90

TYPE OR PRINT NAME

Carolyn L. McKee

(806)378-1000

TELEPHONE NO.

(This space for State Use)

Original Signed by FRANK T. CHAVEZ

APPROVED BY

TITLE

SUPERVISOR DISTRICT # 3

DATE

SEP 17 1990

CONDITIONS OF APPROVAL, IF ANY: