Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED Budget Bureau No. 1004-0135 Expires: March 31, 1993

, **		Expires:	March	מו, ונ	<u></u>
5.	Lease	Designat	ion and	Serial	No.

SF-080854 SUNDRY NOTICES AND REPORTS ON WELLS 6. If Indian, Allottee or Tribe Name Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. . . . Use "APPLICATION FOR PERMIT-" for such proposals 7. If Unit or CA. Agreement Designation SUBMIT IN TRIPLICATE San Juan 32-8 Unit 1. Type of Well 8. Well Name and No. Oil Gas Well 220 2. Name of Operator 9. API Well No. PHILLIPS PETROLEUM COMPANY 30-045-28223 3. Address and Telephone No. 300 West Arrington Suite 200, Farmington, NM 87401 505/599-3400 10. Field and Pool, or Exploratory Area Basin Fruitland Coal 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 11. County or Parish, State Unit L, 1445' FSL & 820' FWL Sec. 24, T31N, R8W San Juan, NM CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 12. TYPE OF ACTION TYPE OF SUBMISSION Change of Plans Abandonment New Construction Recompletion Non-Routine Fracturing Plugging Back NOV2 0 1990 Water Shut-Off Casing Repair Conversion to Injection Altering Casing Final Abandonment CON. DIV. K Other As Per NTL-FRA-90-1 Dispose Water (Note: Report results of multiple completion on Well DIST. 3 Completion or Recompletion Report and Log form.) 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) Description of cement job to fulfill requirements for protection of usable water zones including the Ojo Alamo Formation, as per NTL-FRA-90-1. Time Completed: Time Started: 1430 9-22-90 Casing Size 7" 23# J-55 New Casing Seat 8-3/4" Hole Size 2142 ___. 2187 Turbo Centralizers at 2233 2901 3081 3145 Spring Type Centralizers at 10 Fresh Water. BB1s, Spacer Mud Flush 10 Lead Slurry 500 SX 65/35 POZ.12% Gel.1/4# Flocele/Sk,11.7 ppg @ 2.3 ft3/Sx yield. Mid Slurry -----Tail Slurry 150 SX C1 "G", 1/4# Flocele/Sk, 15.8 ppg @ 1.15 ft3/Sx yield Bbls Fresh Water. Displaced Plug with 122 151 **abbb**//Sacks Volume Cement Circulated PSI, Average Rate 7 BPM, Bumped Plug with 1550 PSI. 400 Average Pressure R. A. Allred 14. I hereby certify ACCEPTED FOR RECORD Title Drilling Supervisor Signed _ (This space for Federal or State office use) NQV 15 1990 Tiele FARMINGTON RESOURCE AREA NMOCD