Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR

FORM APPROVED Budget Bureau No. 1004-0135 Expires: March 31, 1993

BUREAU OF LAND MANAGEMENT	5. Lease Designation and Serial No.
SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals	SF-078996 6. If Indian, Allottoe or Tribe Name
SUBMIT IN TRIPLICATE	7. If Unit or CA, Agreement Designation
1. Type of Well Oil Gas Well Well Other	San Juan 32-7 Unit 8. Well Name and No.
2. Name of Operator PHILLIPS PETROLEUM COMPANY	9. API Well No.
3. Address and Telephone No. 300 West Arrington Suite 200, Farmington, NM 87401 505/599-3400	30-045-28273 10. Field and Pool, or Exploratory Area
4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 1773' FNL & 1035' FEL Sec. 8, T31N, R7V	Basin Fruitland Coal 11. County or Parish, State San Juan, NM
12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPOR	RT, OR OTHER DATA
TYPE OF SUBMISSION TYPE OF ACTION	
Notice of Intent D	Change of Plans New Construction Non-Routine Fracturing Water Shut-Off Conversion to Injection Dispose Water (Not: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)
13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Description of cement job to fulfill requirements for protection of uthe Ojo Alamo Formation, as per NTL-FRA-90-1.	
Date: 12-12-90 Time Started: 1605 Time Commodified Hole Size 8-3/4" Casing Size 7" 23# J-55 New Casing Casing Turbo Centralizers at 2437' 2392' 2353' Spring Type Centralizers at 3066' 3031' 2945' 2858 Mud Flush 10 BBls, Spacer 10 Fresh Water.	-
Lead Slurry 500 Sx 65/35 Poz,12% Gel, 1/4# Flocele/Sk, 11.7 ppg @ 2	2.3 Ft ³ /Sx yield.
Mid Slurry	
Tail Slurry _ 150 Sx Cl B, 1/4# Flocele/Sk, 15.6 ppg @ 1.18 Ft ³ /Sk y	leld.
Displaced Plug with $\underline{120}$ Bbls Fresh Water.	
Volume Cement Circulated 158 Bhks/Sacks Average Pressure 250 PSI, Average Rate 9 BPM, Bumped Pl	ug with 1500 PSI.
14. I hereby certify that the fortgoing is true and correct R. A. Allred Signed Drilling Supervisor	Dute 12-19-90
(This space for Foderal or State office use) ACCEP	TED FOR RECORD
Approved by	AN 1 1 1991 .