Form 3160-5 (June 1990)

## UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

FORM APPROVED

Donker Date	CEU MU.	100-0133	
Expires:	March	31, 1993	

5. Lease Designation and Serial No. SF-079029 SUNDRY NOTICES AND REPORTS ON WELLS 6. If Indian, Allottee or Tribe Name Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals 7. If Unit or CA, Agreement Designation SUBMIT IN TRIPLICATE San Juan 32-8 Unit 1. Type of Well 8. Well Name and No. Oil Gas Well 2. Name of Operator 9. API Well No. PHILLIPS PETROLEUM COMPANY 30-045-28274 3. Address and Telephone No. 300 West Arrington Suite 200, Farmington, NM 87401 505/599-3400 10. Field and Pool, or Exploratory Area Basin Fruitland Coal 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 11. County or Parish, State Unit K, 1718' FSL & 1470' FWL Sec. 3, T31N, R8W San Juan, NM CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 12. TYPE OF ACTION TYPE OF SUBMISSION Change of Plans Abandonment Notice of Intent New Construction Recompletion Non-Routine Fracturing Plugging Back X Subsequent Report Casing Repair Conversion to Injection Altering Casing Final Abandonment Notice Other As Per NTL-FRA-90-1 Dispose Water (Note: Report results of multiple completio 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\* Description of cement job to fulfill requirements for protection of usable water zones including the Ojo Alamo Formation, as per NTL-FRA-90-1. Time Completed: 0625 10-9-90 Time Started: Date: Ft. Casing Size 7" 23# J-55 New Casing Seat (3369) Hole Size 8-3/4" , 2413 Turbo Centralizers at 2451 Spring Type Centralizers at 3350, 3290 BBls, Spacer 10 Fresh Water. Mud Flush 10 Lead Slurry 500 SX 65/35 POZ,12% Gel,1/4# Flocele/Sk, 11.7 ppg @ 2.3 ft<sup>3</sup>/Sx yield. Mid Slurry Tail Slurry 150 SX Cl B, 1/4# Flocele/Sk, 15.6 ppg @ 1.15 ft3/Sx yield. Displaced Plug with 129 Bbls Fresh Water. \_ 数数数/Sacks Volume Cement Circulated 275 PSI, Average Rate 8 BPM, Bumped Plug with 1500 Average Pressure 850 14. I hereby cortify that the foregoing R. A. Allred 10-11-90 Title Drilling Supervisor (This space for Federal or State office use) ACCEPTED FOR RECORD Approved by \_\_\_\_\_\_\_\_, if any: OCT 30 1990 Tide 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the ARMINGTONING EDGLI firstions on fraudulent statements

or representations as to any matter within its jurisdiction.