

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

5. Lease Designation and Serial No.

SF-079029

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

San Juan 32-8 Unit

8. Well Name and No.

241

9. API Well No.

30-045-28275

10. Field and Pool, or Exploratory Area
Basin Fruitland Coal

11. County or Parish, State

San Juan, NM

SUBMIT IN TRIPLICATE

1. Type of Well

Oil Well Gas Well Other

2. Name of Operator

PHILLIPS PETROLEUM COMPANY

3. Address and Telephone No.

300 West Arrington Suite 200, Farmington, NM 87401 505/599-3400

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit A, 1076' FNL & 1012' FEL
Sec. 4, T31N, R8W

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

Notice of Intent

Subsequent Report

Final Abandonment

TYPE OF ACTION

Abandonment

Recompletion

Plugging Back

Casing Repair

Altering Casing

Other As Per NTL-FRA-90-1

Change of Plans

New Construction

Non-Routine Fracturing

Water Shut-Off

Conversion to Injection

Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Description of cement job to fulfill requirements for protection of usable water zones including the Ojo Alamo Formation, as per NTL-FRA-90-1.

Date: 10-13-90 Time Started: 0825 Time Completed: 0937
Hole Size 8-3/4" Casing Size 7" 23# J-55 New Casing Seat 3366' Ft.
Turbo Centralizers at 2489', 2445', 2415'.
Spring Type Centralizers at 3344', 3276', 3188', 3099', 3018'.
Mud Flush 10 Bbls, Spacer 10 Fresh Water.

Lead Slurry 500 SX 65/35 Poz, 12% Gel/1/4# Flocele/Sk, 11.7 ppg @ 2.3 ft³/Sx yield.

Mid Slurry ----

Tail Slurry 150 SX Class G, 1/4# Flocele/Sk, 15.8 ppg @ 1.15 ft³/Sk yield

Displaced Plug with 129 Bbls Fresh Water.

Volume Cement Circulated 144 Bbls/Sacks

Average Pressure 380 PSI, Average Rate 10 BPM, Bumped Plug with 1550 PSI.

14. I hereby certify that the foregoing is true and correct

Signed R. A. Allred

Title Drilling Supervisor

Date 10-25-90

(This space for Federal or State office use)

Approved by _____
Conditions of approval, if any:

Title AMOC

ACCEPTED FOR RECORD

OCT 31 1990

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side