

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

1. Type of Well
GAS

2. Name of Operator

**BURLINGTON
RESOURCES**

OIL & GAS COMPANY

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

1885' FSL, 1130' FWL, Sec. 12, T-31-N, R-9-W, NMPM

5. Lease Number

SF-078508

If Indian, All. or
Tribe Name

Unit Agreement Name

8. Well Name & Number

Nordhaus #715

9. API Well No.

30-045-28314

10. Field and Pool

Basin Fruitland Coal

11. County and State

San Juan Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

☒ Notice of Intent

☐ Abandonment

☐ Change of Plans

☐ Subsequent Report

☐ Recompletion

☐ New Construction

☐ Final Abandonment

☐ Plugging Back

☐ Non-Routine Fracturing

☐ Casing Repair

☐ Water Shut off

☐ Altering Casing

☐ Conversion to Injection

☒ Other - Pump Installation

13. Describe Proposed or Completed Operations

It is intended to install a pump in the subject well according to the attached procedure and wellbore diagram.

RECEIVED
BLM
59 JUN 30 PM 1:51
070 FARMINGTON, NM

14. I hereby certify that the foregoing is true and correct.

Signed [Signature] Title Regulatory Administrator Date 6/29/99
trc

(This space for Federal or State Office use)

APPROVED BY /s/ Duane W. Spencer Title Assistant Secretary Date 6/29/99

CONDITION OF APPROVAL, if any:

Nordhaus #715
PUMPING UNIT INSTALLATION PROCEDURE
6/23/99


Unit L, Section 12, T31N-R9W, San Juan County, New Mexico
Lat. 36.910170 / 36° 54.61'
Long. 107.736530 / 107° 44.19'

1. MIRU pulling unit.
2. NDWH / NU BOP. Kill if necessary with produced Fruitland coal water.
3. PU one joint of tubing and TIH to tag for fill.
4. TOH with 2-3/8" tubing (tbg is set @ 3282'. There are 105 joints of 2-3/8" 4.7# J-55 and an "F" nipple @ 3249').
5. GIH with 2-3/8" 4.7# J-55 EUE tubing with a 4-3/4" bit and clean out to PBTD @ 3322'. Circulate hole clean.
6. TIH w/ 2-3/8" tubing string configured for downhole pump and land @ 3317'. Purge valve will be on bottom, followed by pup joint, perforated sub, and seating nipple. Space out as needed with pup joints.
7. Hang tubing in donut. ND BOP / NUWH.
8. TIH w/ new 1.25" top hold down pump, 3/4" Grade D sucker rods w/ spray metal couplings, polished rod, and polished rod liner. (Note: Vendor contact is listed below)
9. Seat the downhole pump, hang horses head, and space out pump.
10. Load tubing, and pressure test.
11. Start pumping unit and test (adjust spacing as required).
12. RDMO.

COMPLY WITH ALL FEDERAL, STATE AND LOCAL RULES AND REGULATIONS RELATING TO OIL AND GAS OPERATIONS.



Prepared: D.W. Mussett

 6.24.99

Approved: Drilling Supt.

Pump vendor: ENERGY PUMP
Leo Noyes @ 564-2874

Nordhaus #715
June 23, 1999
Basin Fruitland Coal
Unit L, Section 12, T31N, R9W, San Juan County, New Mexico

Completed: 03/21/91

