**UNITED STATES** FORM APPROVED Form 3160-5 Budget Bureau No. 1004-0135 DEPARTMENT OF THE INTERIOR (June 1990) Expires: March 31, 1993 BUREAU OF LAND MANAGEMENT 5. Lease Designation and Serial No. SF-079029 SUNDRY NOTICES AND REPORTS ON WELLS 6. If Indian, Allottee or Tribe Name Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals 7. If Unit or CA, Agreement Designation SUBMIT IN TRIPLICATE 1. Type of Well San Juan 32-8 Unit Well Gas Other 8. Well Name and No. 2. Name of Operator 234 9. API Well No. PHILLIPS PETROLEUM COMPANY 3. Address and Telephone No. 30-045-28324 300 West Arrington Suite 200, Farmington, NM 87401 505/599-3400 10. Field and Pool, or Exploratory Area 4. Location of Well (Footage, Sec., T., K., M., or Survey Description) Basin Fruitland Coal 11. County or Parish, State THE M, 1196' FSL & 1059' FWL Sec. 21, T31N, R8W San Juan, NM CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF ACTION Change of Plans Recompletion **New Construction** JANI 8 1991. Subsequent Report Plugging Back Non-Routine Fracturing Casing Repair Water Shut-Off Altering Casing Conversion to Injection Klother As Per NTL-FRA-90-1 Dispose Water 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) Description of cement job to fulfill requirements for protection of usable water zones including the Ojo Alamo Formation, as per NTL-FRA-90-1. \_ Time Started: 1945 11-18-90  $\_$  Time Completed:  $\_$ Date: Casing Size 7" 23# J-55 New Casing Seat Hole Size 3180' Turbo Centralizers at 2316', 2272' Spring Type Centralizers at 3200' Mud Flush 10 BBls, Spacer 10 Fresh Water. Lead Slurry 500 Sx 65/35 Poz,12% Gel, 1/4# Flocele/Sk,11.7 ppg @ 2.3 Ft<sup>3</sup>/Sx yield. Mid Slurry Tail Slurry 150 Sx Class G,14/# Flocele/Sk, 15.8 ppg @ 1.15 Ft<sup>3</sup>/Sk yield. Displaced Plug with 123 Bbls Fresh Water. 95 Books/Sacks Volume Cement Circulated \_ PSI, Average Rate 7 BPM, Bumped Plug with 1900 PSI. Average Pressure 720

Tide 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United Special any false, fictitious or fraudulent statements

R. A. Allred

(This space for Federal or State office use)

or representations as to any matter within its jurisdicti

Approved by \_\_\_\_\_\_\_\_ if any:

Drilling Supervisor

11-26-90

<del>JAN</del> በ<mark>ሜ 1991</mark>

FARMINGTON RESOURCE AREA