Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

BUREAU OF LAND MANAGEMENT	5. Lease Designation and Serial No.
SUNDRY NOTICES AND REPORTS ON WELLS	SF-078996
Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.	6. If Indian, Allottee or Tribe Name
Use "APPLICATION FOR PERMIT—" for such proposals	
SUBMIT IN TRIPLICATE	7. If Unit or CA, Agreement Designation
1. Type of Well	San Juan 32-7 Unit
Oil Gas Well Other	8. Well Name and No.
2. Name of Operator PHILLIPS PETROLEUM COMPANY	217 9. API Well No.
3. Address and Telephone No.	30-045-28358
300 West Arrington Suite 200, Farmington, NM 87401 505/599-3400	10. Field and Pool, or Exploratory Area
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)	Basin Fruitland Coal
536' FNL & 618' FEL 54, T31N, R7V	II. County or Parish, State San Juan, NM
12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPOR	<u> </u>
TYPE OF SUBMISSION TYPE OF ACTION	
□ Notice of lighter	Change of Plans
Recompletion	New Construction
Subsequent Report 15 15 15 15 Plugging Back	Non-Routine Fracturing
Final Abandoament Notice Altering Casing	Water Shut-Off
Kloha As Per NTI-FRA-90-1	Conversion to Injection Dispose Water
OIST. 3	(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)
Description of cement job to fulfill requirements for protection of u the Ojo Alamo Formation, as per NTL-FRA-90-1. Date: 11-22-90 Time Started: 0830 Time Com	_
Date: 11-22-90 Time Started: 0830 Time Com Hole Size 8-3/4" Casing Size 7" 23# J-55 New Casing	
Turbo Centralizers at 2530', 2491', 2447'.	Seat3256
Spring Type Centralizers at 3235' , 3166' , 3077' , 3000'	,2914 '
Mud Flush 10 BBls, Spacer 10 Fresh Water.	
Lead Slurry 500 Sx 65/35 Poz, 12% Gel, 1/4# Flocele/Sk, 11.7 ppg @	2.3 Ft ³ /Sx yield.
Mid Slurry	
Fail Slurry 150 Sx Class G, 1/4# Flocele/Sk, 15.6 ppg @ 1.18 Ft ³ /S	Sk yield.
Displaced Plug with 125 Bbls Fresh Water.	
Volume Cement Circulated 122 Bloke Sacks	
Average Pressure 325 PSI, Average Rate 8 BPM, Bumped Plu	ng with 1500 PSI.
14. I hereby certify that the spreading is spread correct R. A. Allred	
Signed Title Drilling Supervisor	Detc11-27-90
	CEPTED FOR RECORD
Approved by Title Today:	JAN 03 1391
	JAN US ISSI
Tide 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United St	ANNIAL CO RESOURCE AREA
or representations as to any matter within its jurisdiction.	1.15