

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

PHILLIPS PETROLEUM COMPANY

3. Address and Telephone No.

300 West Arrington Suite 200, Farmington, NM 87401 505/599-3400

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit 1, 681' FSL & 1311' FWL

5. Lease Designation and Serial No.

SP-078996

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

San Juan 32-7 Unit

8. Well Name and No.

218

9. API Well No.

30-045-28359

10. Field and Pool, or Exploratory Area

Basin Fruitland Coal

11. County or Parish, State

San Juan, NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent

☐ Subsequent Report

☐ Final Abandonment

TYPE OF ACTION

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☒ Other As Per NTL-FRA-90-1

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Description of cement job to fulfill requirements for protection of usable water zones including the Ojo Alamo Formation, as per NTL-FRA-90-1.

Date: 12-3-90 Time Started: 1122 Time Completed: 0017
Hole Size 8-3/4" Casing Size 7" 23# J-55 New Casing Seat 3231.96 Ft.
Turbo Centralizers at 2467, 2422, 2382
Spring Type Centralizers at 3187, 3143, 3058, 2969, 2890
Mud Flush 10 Bbls, Spacer 10 Fresh Water.

Lead Slurry 500 Sx 65/35 Poz, 12% gel, 1/4# Flocele/Sk, 11.7 ppg @ 2.3 Ft³/Sk yield.

Mid Slurry -----

Tail Slurry 150 Sx C1 B, 1/4# Flocele/Sk, 15.6 ppg @ 1.18 Ft³/Sk yield.

Displaced Plug with 124 Bbls Fresh Water.

Volume Cement Circulated 156 Bbls/Sacks

Average Pressure 425 PSI, Average Rate 7 BPM, Bumped Plug with 1600 PSI.

14. I hereby certify that the foregoing is true and correct

Signed

R. A. Allred

R. A. Allred

Title Drilling Supervisor

Date 12-12-90

(This space for Federal or State office use)

ACCEPTED FOR RECORD

Approved by

Conditions of approval, if any:

Title

JAN 11 1991

FARMINGTON RESOURCE AREA

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See instruction on Reverse Side

NMCCD