Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR

FORM APPROVED Budget Bureau No. 1004-0135 Expires: March 31, 1993

BUREAU OF LAND MANAGEMENT 5. Lease Designation and Serial No. SF-078996 SUNDRY NOTICES AND REPORTS ON WELLS 6. If Indian, Allottee or Tribe Name Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals 7. If Unit or CA, Agreement Designation SUBMIT IN TRIPLICATE San Juan 32-7 Unit I. Type of Well Oil Gas Other 8. Well Name and No. 213 2. Name of Operator 9. API Well No. PHILLIPS PETROLEUM COMPANY 30-045-28361 3. Address and Telephone No. 300 West Arrington Suite 200, Farmington, NM 87401 505/599-3400 10. Field and Pool, or Exploratory Area 4. Location of Well (Footage, Sec., T., K., M., or Survey Description) Basin Fruitland Coal 11. County or Parish, State 7. 706' FSL & 985' FEL Second, TOIN, R/W San Juan, NM CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 12. TYPE OF FEMILISMON: " TYPE OF ACTION Abandonment Change of Plans Recompletion New Construction Subsequent Report 199 Plugging Back Non-Routine Fracturing Casing Repair Water Shut-Off Alterine Casine Conversion to Injection Mother As Per NTL-FRA-90-1 Dispose Water Completion or Recompletion Report and Log form.) 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled. give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Description of cement job to fulfill requirements for protection of usable water zones including the Ojo Alamo Formation, as per NTL-FRA-90-1.

 Date: 11-18-90 Time Started: 1030 Time Completed: 1130

 Hole Size 8-3/4"
 Casing Size 7" 23# J-55 New Casing Seat 3048

 Turbo Centralizers at 2392' , 2347' , 2303' .

 Spring Type Centralizers at 3035' , 3002' , 2912' , 2831' , 2761' .

 Mud Flush 10 BBls, Spacer 10 Fresh Water.

Ft. Lead Slurry 500 Sx 65/35 Poz, 12% Gel, 1/4# Flocele/Sk, 11.7 ppg @ 2.3 Ft 3/Sx yield. Mid Slurry ----Tail Slurry 150 Sx Cl B, 1/4# Flocele/Sk, 15.6 ppg @ 1.18 Ft3/Sk yield. Displaced Plug with 116 Bbls Fresh Water. 210 Bibbles / Sacks Volume Cement Circulated ____ PSI, Average Rate 8 BPM, Bumped Plug with 1500 PSI. Average Pressure 400 14. I hereby certify that the foregoing R. A. Allred Title Drilling Supervisor ACCEPTED FOR RECORD 9-90 (This space for Federal or State office use) JAN 03 1991

FARMINGTON RESOURCE AREA

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or against the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction