

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

1. TYPE OF WELL SWD		5. LEASE NUMBER SF-078438
2. OPERATOR MERIDIAN OIL INC.		6. IF INDIAN, ALL. OR TRIBE N.
3. ADDRESS & PHONE NO. OF OPERATOR P O BOX 4289 FARMINGTON, NM 87499		7. UNIT AGREEMENT NAME SAN JUAN 32-9 UNIT
4. LOCATION OF WELL 15'FNL 240'FEL		8. FARM OR LEASE NAME SAN JUAN 32-9 UNIT
		9. WELL NO. 5
		10. FIELD, POOL, OR WILDCAT WILDCAT <i>MARR. / ENTRY</i>
		11. SEC. T. R. M OR BLK. SEC. 18 T31N R09W NMPM
14. PERMIT NO. 30-045-28563	15. ELEVATIONS 6605'GL	12. COUNTY SAN JUAN
		13. STATE NM

16. SUBSEQUENT REPORT OF: SPUD

17. Describe proposed or completed operations

SPUD DATE: 081791 SPUD TIME: 0130

TD 321' ran 8 jts of 13 1/8" 54.5# K-55 csg, 306' set @ 319'. Cemented with 363 sks of Class 'G' cmt with 1/4# Flocele/sk, 3% CaCl2, (417 cu ft). Circ. 33 bbls to surface. WOC 12 hours. PT to 600 psi for 30 min.

DATE: 082591

TD 3900', ran 39 jts of 9 5/8" 36.0# HC80 casing, 3887' set @ 3900'. Stage tool @ 2793', ECP @ 2795', Float collar @ 3853', and cement nose guide shoe @ 3900'. Stage 1. Lead with 40 sks of Class G cement 65/35 Poz, 2% CaCl2, 6% gel, 5# gilsonite/sk, and 1/4# Flocele/sk, (71 cu ft). Tail with 90 sacks of Class G cement with 2% CaCl2, (106 cu ft). Circ 6 bbls to surface. Stage 2. Lead with 840 sks of Class G cement 65/35 Poz, 6% gel, 2% CaCl2, 5# gilsonite/sk, and 1/4# Flocele/sk, (1487 cu ft.). Tail with 80 sks of Class G cement with 2% CaCl2, (94 cu ft.). Circ 55 bbls to surface. WOC 12 hours.

18. AUTHORIZED BY:

[Signature]
REGULATORY AFFAIRS

9-19-91
DATE

NOTE: THIS FORMAT IS ISSUED IN LIEU OF US BLM FORM 3160-5.

=====
(This space for Federal or State office use)

APPROVED BY
CONDITION OF APPROVAL, IF ANY:

TITLE

DATE

OCT 11 1991

NMOOD

ACCEPTED FOR RECORD
FARMINGTON RESOURCE AREA
4-11