

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

~~CONFIDENTIAL~~

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT - " for such proposals

RECEIVED
DEC 17 1993

1. Type of Well
☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Amoco Production Company

Attention:

Julie L. Acevedo

3. Address and Telephone No.

P.O. Box 800 Denver, Colorado 80201

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1080 FSL, 1015 FWL

Section

17

Township

31N

Range

R6W

5. Lease Designation and Serial No.

SF-078766

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

Rosa Unit

8. Well Name and No.

Rosa Unit /DK/ 96

9. API Well No.

3004528983

10. Field and Pool, or Exploratory Area

Basin Dakota

11. County or Parish, State

San Juan, New Mexico

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

TYPE OF ACTION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Spud

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Spud a 17.5" surface hole on 8/16/93 at 17:30 hrs. Drilled to 406'.

Set 13.375" 61# K-55 surface casing at 405'. Cemented with 620sx C1 B. Circulated 57 BBLS to the surface.

Pressure tested casing to 1400 psi. Drilled a 12.25" hole to a depth of 3753' on 8/29/93. Set 9.625" 36# K-55 intermediate casing at 3757'. Cemented with 95BBLS C1 B, 212 BBLS C1 B, Tail 25 BBLS C1 B. Circulated 38 BBLS to the surface. Pressure tested casing to 1500 psi.

Drilled a 8.75" hole to a depth of 7820' on 9/5/93. Set 7" 23# K-55 protective casing at 7820'. Cemented with 490 sx CL B, 310 sx CL B. TOC @ 2800'.

Drilled a 6.25" hole to a TD depth of 8125' on 9/15/93. Set 4 1/2" 11.6# N-80 Production Liner, Top at 7609', Bottom at 8124'. cemented with 85sx C1 G. TOC @ 7609'.

Rig released at 24:00 hrs. on 9/15/93.

14. I hereby certify that the foregoing is true and correct

Signed

Julie L. Acevedo

Title

Sr. Staff Assistant

Date

11-8-93

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any:

ACCEPTED FOR RECORD

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious, or fraudulent statements or representations as to any matter within its jurisdiction.

NMOCD

SECRET

CONFIDENTIAL