

submitted in lieu of Form 3160-5

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

1. Type of Well  
GAS

2. Name of Operator  
**BURLINGTON  
RESOURCES** OIL & GAS COMPANY

3. Address & Phone No. of Operator  
PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M  
1450' FNL, 990' FWL, Sec. 9, T-31-N, R-9-W, NMPM

5. Lease Number  
SF-080376

6. If Indian, All. or  
Tribe Name

7. Unit Agreement Name  
San Juan 32-9 Unit

8. Well Name & Number  
San Juan 32-9 U#113

9. API Well No.  
30-045-28987

10. Field and Pool  
Basin Dakota

11. County and State  
San Juan Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

| Type of Submission                                    | Type of Action                                   |
|-------------------------------------------------------|--------------------------------------------------|
| <input type="checkbox"/> Notice of Intent             | <input checked="" type="checkbox"/> Abandonment  |
| <input type="checkbox"/> Subsequent Report            | <input type="checkbox"/> Recompletion            |
| <input checked="" type="checkbox"/> Final Abandonment | <input type="checkbox"/> Plugging Back           |
|                                                       | <input type="checkbox"/> Casing Repair           |
|                                                       | <input type="checkbox"/> Altering Casing         |
|                                                       | <input type="checkbox"/> Other -                 |
|                                                       | <input type="checkbox"/> Change of Plans         |
|                                                       | <input type="checkbox"/> New Construction        |
|                                                       | <input type="checkbox"/> Non-Routine Fracturing  |
|                                                       | <input type="checkbox"/> Water Shut off          |
|                                                       | <input type="checkbox"/> Conversion to Injection |

13. Describe Proposed or Completed Operations

6-22-00 MIRU. SDON.

6-23-00 ND WH. NU BOP. TOOH 2 3/8" tbg. TIH w/gauge ring to 8060'. TIH w/CIBP, set @ 7950'. SD for weekend.

6-26-00 PT csg to 500 psi/10 min, CK. Plug #1: pump 44 sx Class "B" cmt above CIBP to 7518'. Plug #2: pump 33 sx Class "B" cmt inside 7" csg @ 7210-7034'. Plug #3: pump 29 sx Class "B" cmt inside 7" csg @ 5164-5009'. Plug #4: pump 30 sx Class "B" cmt inside 7" csg @ 4386-4226'. Plug #5: pump 29 sx Class "B" cmt inside 7" csg @ 3919-3764'. Perf 3 sqz holes @ 3618'. Circ hole clean. SDON.

6-27-00 ND BOP. Weld on 7" csg collar. Jet cut 7" csg @ 3555'. PU on csg pulling to 97,000#; not free. Rigs matting started caving in. NU BOP. TIH w/tbg to 3668'. Set slips on top of BOP. RD. Fix matting on rig w/T-seal & wider boards. RU. TOOH w/tbg. SDON.

6-28-00 ND BOP. PU on csg; not free. TIH w/csg splitter & split csg in collar @ 3542'. PU on csg; csg still stuck. Ran CBL @ 3738'-surface. TOC on 7" csg @ 1600'. Cut csg collar off & dress 7" stub. NU BOP. SDON.

Continued on back

14. I hereby certify that the foregoing is true and correct.

Signed [Signature] Title Regulatory Supervisor Date 7/12/00

(This space for Federal or State Office use)

APPROVED BY \_\_\_\_\_ Title \_\_\_\_\_ Date \_\_\_\_\_

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

ACCEPTED FOR RECORD

JUL 17 2000

OFFICE

6-29-00 (Verbal approval from Steve Mason, BLM, to plug well w/7" csg still in well).  
TIH w/pkr, set @ 3386'. PT 9 5/8" csg to 600 psi/5 mins, OK. Plug #6: pump  
58 sx Class "B" cmt @ 3618-3442', sqz 25 sx outside 7" csg & leave 33 sx  
inside 7" csg. TOOH w/pkr. Perf 3 sqz holes @ 3175'. TOOH. TIH w/pkr, set  
@ 2954'. Plug #7: pump 50 sx Class "B" cmt @ 3175-3025', sqz 21 sx outside  
7" csg & leave 28 sx inside 7" csg. TOOH w/pkr. Perf 3 sqz holes @ 2265'.  
TIH w/pkr, set @ 1990'. Plug #8: pump 71 sx Class "B" cmt @ 2265-2051', sqz  
30 sx outside 7" csg & leave 40 sx inside 7" csg. TOOH w/ pkr. Perf 6 sqz  
holes @ 654'. Est circ down 7" & out 9 5/8". TIH w/cmt ret, set @ 591'. SDON.

6-30-00 Plug #9: pump 105 sx Class "B" cmt @ 654-504', sqz 22 sx in the 7" x 9 5/8"  
annulus & 54 sx outside the 9 5/8" csg, left 12 sx below cmt ret & 17 sx  
above up to 504'. Perf 3 sqz holes @ 471'. Plug #10: pump 306 sx Class "B"  
cmt down 7" csg @ 471'-surface. Circ good cmt out bradenhead & 9 5/8" annulus.  
WOC. ND BOP. Dig out WH & cut off. Install dry hole marker w/40 sx Class "B"  
cmt. RD. Rig released. (Marco Kecman, BLM, was on location) Well plugged and  
abandoned on 6-30-00.