

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT - " for such proposals

RECEIVED
BLM

RECEIVED
FEB 14 1994

070 FARMINGTON, NM

5. Lease Designation and Serial No.

SF-080597

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Amoco Production Company

Attention:

D. Tallant

3. Address and Telephone No.

P.O. Box 800 Denver, Colorado 80201

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1510'FSL

1460'FEL

Section 26 Township 30N Range 8W

8. Well Name and No.

Tallant #1

9. API Well No.

30-045-29054

10. Field and Pool, or Exploratory Area

Basin Dakota

11. County or Parish, State

San Juan New Mexico

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

TYPE OF ACTION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Spud & Set

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Spud a 17.5" surface hole on 1/22/94 at 07:00 hrs. Drilled to 445'.

Set 13.375" 61# J-55 surface casing at 440'. Cemented with 500 SX CL B. Circulated 55 BBLS to the surface.

Pressure tested casing to 1000 psi. Drilled a 12.250" hole to a depth of 3030' on 1/29/94. Set 9-5/8" 36# J-55 intermediate

casing at 3030'. Cemented with 1st Stg=300 SX CL B, 2nd Stg=675 SX CL B, Tail w/100 SX CL B. Circulated 0 BBLS to the surface. Pressure tested casing to 1500 psi.

Drilled a 8.750" hole to a depth of 6990' on 2/1/94. Set 7" 23# J-55 protective casing at 6984'. Cemented with 775 SX 50/50 POZ CL A. TOC @ 2600'.

Drilled a 6.250" hole to a TD depth of 7435' on 2/3/94. Set 4.5", 11.6#, N-80 Production Liner, Top at 6749', Bottom at 7435'. cemented with 100 SX CL B. TOC @ 6749'.

Rig released at 20:00 hrs. on 2/3/94.

14. I hereby certify that the foregoing is true and correct

Signer

DeAnne Tallant

Title

Staff Assistant

Date

02-08-1994

(This space for Federal or State office use)

Approved by

Title

Conditions of approval, if any:

ACCEPTED FOR RECORD

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

* See Instructions on Reverse Side

NMOCD

BY

FARMINGTON DISTRICT OFFICE

Sum

FEB 15 1994