

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a well or to a different reservoir.
Use "APPLICATION FOR PERMIT - " for such proposals

RECEIVED
BLM

34 MAR -7 AM 11:52

070 FARMINGTON, NM

5. Lease Designation and Serial No.

SF-078195

6. If Indian, Allottee or Tribe Name

7. II Unit or CA, Agreement Designation

8. Well Name and No.

Sellers Federal LS #2M

9. API Well No.

30-045-29080

10. Field and Pool, or Exploratory Area

Mesa Verde / Basin Dakota

11. County or Parish, State

San Juan, NM

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

AMOCO PRODUCTION COMPANY

3. Address and Telephone No.

P.O. Box 800 Denver, Colorado 80201

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1170' FSL, 1460' FEL

Attention:

D. Tallant

(303) 830-5427

Section 30 Township 30N Range 10W

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

TYPE OF ACTION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment Notice

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☒ Other Spud + Set

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Spud a 14.750" surface hole on 2/3/94 at 1230 hrs. Drilled to 267

Set 11.75" 42# H-40 surface casing at 267'. Cemented

185 SX CL B Circulated 5 BBLS to the surface

Pressure tested casing to 1000 psi. Drilled a 11.0" hole to a depth of

2778' on 2/9/94. Set 8.625" 32# K-55 intermediate

casing at 2778'. Cemented with 1st sk = 190 SX CL B, 2nd sk = 150 SX POZ, Tail w/ 100 SX CL B.

Circulated 42 BBLS to the surface. Pressure tested casing to 2000 psi.

Drilled a 7.875" hole to a TD depth of 7164' on 2/14/94 Set 5.5", 15.5", K-55 Long

String from Surface to bottom at 7152' cemented with 1150 SX 50/50 POZ TOC @ 2300'.

Rig released at 2400 hrs. on 2/14/94.

14. I hereby certify that the foregoing is true and correct

Signed

DeAnn Tallant

Title

Staff Assist

Date

2-28-94

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:

Title

ACCEPTED FOR RECORD

Date

MAR 11 1994

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious, or fraudulent statements or representations as to any matter within its jurisdiction.

NMOCD

* See Instructions on Reverse Side

BY

Sm

FARMINGTON DISTRICT OFFICE