UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Well			
		5.	Lease Number SF-078319
. Type of Well GAS	, with a second	6.	
		7.	Unit Agreement Name
Name of Operator			
MERIDIAN OIL		8.	Well Name & Number
3. Address & Phone No. of Operator		٥	Riddle E #1R API Well No.
PO Box 4289, Farmington, NM 87499 (505) 326-9700		۶.	30-045-29207
Location of Well, Footage, Sec., T, R, M 1045'FSL, 1470'FEL, Sec.4, T-30-N, R-9-W, NMPM		10.	Field and Pool Blanco Mesaverde
1010 LDD, 1170 LDD, Sec. 1, 1 30 N, N 3 N, MILL		11.	County and State San Juan Co, NM
2. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,		THER	DATA
Type of Submission Type of Act Notice of Intent Abandonment	ion Change c	of Pla	ins
Recompletion	New Cons	truct	ion
X Subsequent Report Plugging Back Casing Repair	Non-Rout Water Sh		
Final Abandonment Altering Casing X Other - Spud	Conversi	on to	Injection
A other space			
13. Describe Proposed or Completed Operations 4-16-95 MIRU. Spud well @ 10:15 p.m. 4-15-95. D	Orill to 24	15'. T	COOH. TIH w/5 jts
3. Describe Proposed or Completed Operations	mtd w/160 9 cu.ft.). side. NU E psi.OK.	sx Cl Cmt 30P. P WOC.	ass "G" cmt w/3% 12' from surface. Cump 7 sx Class "G" Drilling ahead.
13. Describe Proposed or Completed Operations 4-16-95 MIRU. Spud well @ 10:15 p.m. 4-15-95. D 9 5/8" 36# K-55 STC csg, set @ 237'. C calcium chloride, 0.25 pps Flocele (18 WOC. Pump 5 sx Class "G" cmt down back	mtd w/160 9 cu.ft.). side. NU E psi.OK.	sx Cl Cmt 30P. P WOC.	ass "G" cmt w/3% 12' from surface. Cump 7 sx Class "G" Drilling ahead.
Describe Proposed or Completed Operations 4-16-95 MIRU. Spud well @ 10:15 p.m. 4-15-95. D 9 5/8" 36# K-55 STC csg, set @ 237'. C calcium chloride, 0.25 pps Flocele (18 WOC. Pump 5 sx Class "G" cmt down back	mtd w/160 9 cu.ft.). side. NU E psi.OK.	SX C1 Cmt SOP. P	ass "G" cmt w/3% 12' from surface. Cump 7 sx Class "G" Driffling ahead.
Describe Proposed or Completed Operations 4-16-95 MIRU. Spud well @ 10:15 p.m. 4-15-95. D 9 5/8" 36# K-55 STC csg, set @ 237'. C calcium chloride, 0.25 pps Flocele (18 WOC. Pump 5 sx Class "G" cmt down back	mtd w/160 9 cu.ft.). side. NU E psi.OK.	SX C1 Cmt SOP. P	ass "G" cmt w/3% 12' from surface. Cump 7 sx Class "G" Drilling ahead.
13. Describe Proposed or Completed Operations 4-16-95 MIRU. Spud well @ 10:15 p.m. 4-15-95. D 9 5/8" 36# K-55 STC csg, set @ 237'. C calcium chloride, 0.25 pps Flocele (18 WOC. Pump 5 sx Class "G" cmt down back	mtd w/160 9 cu.ft.). side. NU E psi OK	SX C1 Cmt SOP. P WOC.	ass "G" cmt w/3% 12' from surface. Cump 7 sx Class "G" Driffling ahead.
13. Describe Proposed or Completed Operations 4-16-95 MIRU. Spud well @ 10:15 p.m. 4-15-95. D 9 5/8" 36# K-55 STC csg, set @ 237'. C calcium chloride, 0.25 pps Flocele (18 WOC. Pump 5 sx Class "G" cmt down back cmt down backside. PT csg & BOP to 600	mtd w/160 9 cu.ft.). side. NU E psi OK.	SX C1 Cmt SOP. P WOC.	EIVED 2 4 1995
4-16-95 MIRU. Spud well @ 10:15 p.m. 4-15-95. D 9 5/8" 36# K-55 STC csg, set @ 237". C calcium chloride, 0.25 pps Flocele (18 WOC. Pump 5 sx Class "G" cmt down back cmt down backside. PT csg & BOP to 600	mtd w/160 9 cu.ft.). side. NU E psi OK.	SX C1 Cmt SOP. P WOC.	EIVED 2 4 1995
13. Describe Proposed or Completed Operations 4-16-95 MIRU. Spud well @ 10:15 p.m. 4-15-95. D 9 5/8" 36# K-55 STC csg, set @ 237'. C calcium chloride, 0.25 pps Flocele (18 WOC. Pump 5 sx Class "G" cmt down back cmt down backside. PT csg & BOP to 600 Signed Title Regulatory Aff (This space for Federal or State Office use) APPROVED BY	mtd w/160 9 cu.ft.). side. NU E psi OK.	SX C1 Cmt SOP. P WOC. APR	EIVED 2 4 1995
13. Describe Proposed or Completed Operations 4-16-95 MIRU. Spud well @ 10:15 p.m. 4-15-95. D 9 5/8" 36# K-55 STC csg, set @ 237'. C calcium chloride, 0.25 pps Flocele (18 WOC. Pump 5 sx Class "G" cmt down back cmt down backside. PT csg & BOP to 600 Signed Title Regulatory Aff (This space for Federal or State Office use) APPROVED BY	mtd w/160 9 cu.ft.). side. NU E psi OK Correct. fairs Dat	SX C1 Cmt BOP. P WOG. APR	EIVED 2 4 1995
13. Describe Proposed or Completed Operations 4-16-95 MIRU. Spud well @ 10:15 p.m. 4-15-95. D 9 5/8" 36# K-55 STC csg, set @ 237'. C calcium chloride, 0.25 pps Flocele (18 WOC. Pump 5 sx Class "G" cmt down back cmt down backside. PT csg & BOP to 600 14. I hereby certify that the foregoing is true and c Signed Manual Title Regulatory Aff (This space for Federal or State Office use)	mtd w/160 9 cu.ft.). side. NU E psi OK Correct. fairs Dat	SX C1 Cmt SOP. P WOG. APR te 4/	EVED 2 4 1995 /17/95