

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT - " for such proposals

5. Lease Designation and Serial No.

SF-081239

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

L.C. Kelly

#5A

9. API Well No.

3004529252

10. Field and Pool, or Exploratory Area

Blanco Mesaverde

11. County or Parish, State

San Juan

New Mexico

1. Type of Well

☐ Oil Well

☒ Gas Well

☐ Other

2. Name of Operator

Amoco Production Company

Attention:

Patty Haeefe

3. Address and Telephone No.

P.O. Box 800, Denver, CO 80201

(303) 830-4988

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1540' FNL

1490' FEL

Sec. 3 T 30N R 12W

Unit G

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

TYPE OF ACTION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment Notice

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☒ Other Spud and Set Casing

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

MIRU spud rig. Spud a 12.25" conductor hole on 09/25/95 at 11:50 hrs. Drilled to 85'. Set 8.625" 24# K-55 conductor pipe at 85'. Cement with 60 sx Class B. Cement pipe to surface. Rig released 9/25/95.

Drill a 6.75" surface hole on 10/24/95 at 18:00 hrs. Drilled to 2515'. Set 5.5" 14# CF-50 surface casing at 2484'. Cemented with 200 sx Class B 50/50 poz, cement did not get to top - est cement top is 10 bbls down; temp survey found cement top at 600'. Pressure test casing to 1797 psi.

Drilled a 4.75" hole to a depth of 4928' on 10/29/95. Set 2.875" 6.4 # N-80 production casing at 4915 ft. Cemented with 225 sx Class B 50/50 poz. TOC 2000'. Rig released at 10:00 hrs on 10/29/95.

14. I hereby certify that the foregoing is true and correct

Signed

Patty Haeefe

Title

Staff Assistant

Date

11-05-1995

(This space for Federal or State office use)

Approved by

Title

Conditions of approval, if any:

ACCEPTED FOR RECORD

NOV 27 1995

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious, or fraudulent statements or representations as to any matter within its jurisdiction.

NMOCB

* See Instructions on Reverse Side

FARMINGTON DISTRICT OFFICE

RY