

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

RECEIVED
BLM MAIL ROOM

RECEIVED
MAR - 1996
OIL CONT. DIV.

55 FEB 23 AM 11:53

070 FARMINGTON, NM

1. Type of Well
GAS

2. Name of Operator
MERIDIAN OIL

3. Address & Phone No. of Operator
PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M
1830' FNL, 1490' FWL, Sec. 28, T-30-N, R-11-W, NMPM

5. Lease Number
SF-078138
If Indian, All. or
Tribe Name

7. Unit Agreement Name

8. Well Name & Number
Morris ~~Com~~ #100

9. API Well No.
30-045-29327

10. Field and Pool
Blanco Mesaverde

11. County and State
San Juan Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission	Type of Action
☐ Notice of Intent	☐ Abandonment
☒ Subsequent Report	☐ Recompletion
☐ Final Abandonment	☐ Plugging Back
	☐ Casing Repair
	☐ Altering Casing
	☒ Other -
	☐ Change of Plans
	☐ New Construction
	☐ Non-Routine Fracturing
	☐ Water Shut off
	☐ Conversion to Injection

13. Describe Proposed or Completed Operations

2-15-96 Drill to 2166'. TOOH, circ hole clean. TIH for core #1: 2167-2196', cut 30', recovered 28.5'. TOOH. TIH, ream @ 2167-2196'. Drill @ 2196-2600'. Circ hole clean. TOOH. RU, log.

2-16-96 Log. RD. Circ hole clean. TIH w/58 jts 7" 20# K-55 ST&C csg, set @ 2599'. Cmt d w/281 sx Class "B" 50/50 poz w/25% Silica flour, 25 pps Cellophane, 25 pps Gilsonite (663 cu.ft.). Tailed w/100 sx Class "B" neat cmt w/2% calcium chloride, 25 pps Cellophane (118 cu.ft.). Circ 18 bbl cmt to surface. WOC. NU BOP. PT csg to 1500 psi, OK.

2-17-96 Drill @ 2600-3719'.

2-18-96 Drill @ 3719-3879'. Blow well clean. TOOH. TIH w/core #2: 3879-3909', cut 30', recovered 29.7'. TOOH. TIH w/core #3: 3909-3939'.

2-19-96 Cut 30', recovered 29.8'. TOOH. TIH w/core #4: @ 3939-3969', cut 30', recovered 29.5'. TIH, drill @ 3936-4344'.

2-20-96 Drill to TD @ 5000'. Circ hole clean. TOOH. RU, log.

2-21-96 Logging.

2-22-96 TOOH. TIH w/60 jts 4 1/2" 10.5# K-55 ST&C lnr, set @ 4947'. Top of lnr @ 2380'. Cmt d w/365 sx Class "B" 50/50 poz w/3% Halad-344, 3 pps Gilsonite, 0.25 pps Cellophane (478 cu.ft.). Reverse out 19 bbl cmt. WOC. PT lnr to 3000 psi/15 min, OK. ND BOP. NU WH. RD. Rig released.

14. I hereby certify that the foregoing is true and correct.

Signed [Signature] Title Regulatory Administrator Date 2/23/96

(This space for Federal or State Office use)

APPROVED BY _____ Title _____

CONDITION OF APPROVAL, if any:

Date **ACCEPTED FOR RECORD**

FEB 29 1996

FARMINGTON DISTRICT OFFICE

BY 549

NMOCD