

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
SUNDRY NOTICES AND REPORT ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT" - for such proposals.

RECEIVED
BLM

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

5. Lease Designation and Serial No.

ANNO03586

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

8. Well Name and No.

Stewart LS 6M

2. Name of Operator

Amoco Production Company

Attention:

Patty Haeefe

9. API Well No.

3004529380

3. Address and Telephone No.

P.O. Box 800, Denver, Colorado 80201

(303) 830-4988

10. Field and Pool, or Exploratory Area

Blanco Mesaverde/Basin Dakota

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

800' FSL & 1165' FEL

Section 28 T30N R10W Unit P

11. County or Parish, State

San Juan, New Mexico

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

TYPE OF ACTION

☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Spud & Casing

☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log Form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

MIRU spud rig. Spud a 12.25" surface hole on 8/8/96 at 15:00 hrs. Drilled to 176'. Set 9.625" 36# J-55 surface pipe at 171'. Cement with 100 sx Class B. Cement pipe to surface. Rig released 8/8/96.

Drilled an 8.750" hole on 9/10/96. Drilled to 3025'. Set 7.000" 23# CF-50 intermediate casing at 3008'. Cemented with 390 sx Class B 50/50 poz, tail with 100 sx Class B. Circulated 30 bbls to surface. Pressure test casing to 2200 psi. DV tool at 5350'.

Drilled a 6.25" hole to a depth of 7369' on 9/13/96. Set 4.500" 10.5# J-55 production casing at 7348 ft. Cemented with 475 sx Class B 50/50 poz. Pressure test casing to 1950 psi. Ran temp survey, TOC at 2300'. Rig released at 01:00 hrs on 9/15/96.

RECEIVED
OCT - 2 1996

ACCEPTED FOR RECORD

SEP 27 1996

OIL CON. DIV.
DIST. 3

FARMINGTON DISTRICT OFFICE

BY

14. I hereby certify that the foregoing is true and correct

Signed

Patty Haeefe

Title

Staff Assistant

Date

09/23/96

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious, or fraudulent statement or representations as to any matter within its jurisdiction.

NMOC