

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

## Sundry Notices and Reports on Wells

1. Type of Well  
GAS

2. Name of Operator

**BURLINGTON  
RESOURCES**

OIL & GAS COMPANY

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

1615' FSL 2200' FEL, Sec. 23, T-31-N, R-9-W, NMPM

5. Lease Number  
NM-03601

6. If Indian, All. or  
Tribe Name

7. Unit Agreement Name

**OIL CON. DIV.  
DIST. 8**

Well Name & Number  
Seymour #7A

9. API Well No.  
30-045-29399

10. Field and Pool  
Blanco Mesaverde

11. County and State  
San Juan Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

☒ Notice of Intent

☐ Subsequent Report

☐ Final Abandonment

Type of Action

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☒ Other -

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut off

☐ Conversion to Injection

13. Describe Proposed or Completed Operations

It is intended to install a pump in the subject well according to the attached procedure.

14. I hereby certify that the foregoing is true and correct.

Signed [Signature] (MEL5) Title Regulatory Administrator Date 2/9/99

(This space for Federal or State Office use)

APPROVED BY /S/ Duane W. Spencer

Title San Juan Petroleum Management Date 2/9/99

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

Seymour #7A  
Mesaverde  
1615' FSL, 2200' FEL  
Unit J, Section 23, T-31-N, R-9-W  
Latitude / Longitude: 36° 52.8561' / 107° 44.8809'  
DPNO: 2579101  
**Rod Pump Installation Procedure**

1. Install used C-160 pumping unit.
2. Hold safety meeting. Comply with all NMOCD, BLM and Burlington safety and environmental regulations. Prior to moving in rig, make one-call and then verify rig anchors and dig pit.
3. MOL and RU workover rig. Obtain and record all wellhead pressures. NU relief line. Blow well down and kill with 2% KCL water if necessary. ND WH and NU BOP with stripping head. Test and record operation of BOP rams. Have wellhead and valves serviced as necessary. Test secondary seal and replace/install as necessary.
4. Mesaverde, 2-3/8", 4.7# J-55 tubing is set at 5780'. Broach tubing and set tubing plug in tubing at 5727'. Fill tubing with half of its volume of 2% KCL to insure the tubing plug will be held in place. Release donut; pick up additional joints of tubing and tag bottom. (Record depth). TOOH with tubing. PBTD should be at ±5876'. Visually inspect tubing for corrosion and replace any bad joints. Remove any unnecessary equipment (i.e. Tbg stop, bumper spring, etc.). Check tubing for scale build up and notify Operations Engineer.
5. PU and TIH with 3-7/8" bit, bit sub and watermelon mill on 2-3/8" tubing and round trip to below perforations, cleaning out with air/mist. **NOTE: When using air/mist, minimum mist rate is 12 bph.** If scale is present, contact Operations Engineer to determine methodology for removing scale from casing and perforations.
6. Rabbit all tubing prior to TIH. TIH with one joint of 2-3/8" 4.7# tubing, 4' perforated sub, in-line check, 1.78" seating nipple, and then remaining 2-3/8" tubing. Replace any bad joints.
7. Land tubing at ±5814'. **NOTE: If excessive fill is encountered, discuss this landing depth with Operations Engineer.** Pump off check valve. ND BOP and NU WH.
8. If fill was encountered, contact Operations Engineer to discuss possibility of running a sand screen on the pump. PU and TIH with 2" x 1.25" x 10' x 14' RHAC-Z insert pump, from Energy Pump & Supply, 1 1-1/4" sinker bar (5/8" pin with 3/4" crossover), 3/4" Grade D rods with spray-metal couplings to 2653', and molded paraffin scrapers to surface. Test pump action and hang rods on pumping unit. RD and MOL. Return well to production.

Recommended: M.E. Lutey  
Operations Engineer

Approved:

Bruce W. Boyer 1.27.99  
Drilling Superintendent

Operations Engineer: Mary Ellen Lutey  
Office - (599-4052)  
Home - (325-9387)  
Pager - (324-2671)

Pump and Rods: Energy Pump & Supply  
Leo Noyes  
Office - (564-2874)