

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

COPY

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT-" for such proposals

SUBMIT IN TRIPLICATE

1. TYPE OF WELL

OIL WELL ☐ GAS WELL ☒ OTHER ☐

2. NAME OF OPERATOR

CONOCO INC.

3. ADDRESS AND TELEPHONE NO.

10 Desta Drive, Ste. 100W Midland, Texas 79705-4500 (915-686-5424)

4. LOCATION OF WELL (Footage, Sec., T., R., M., or Survey Description)

820' FNL & 1605' FWL, UNIT LETTER 'C', SEC 31, T-30-N, R-10-W

5. LEASE DESIGNATION AND SERIAL NO.

SF 078194

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. IF UNIT OR CA, AGREEMENT DESIGNATION

LUDWICK LS

8. WELL NAME AND NO.

21M

9. API WELL NO.

30-045-29565

10. FIELD AND POOL, OR EXPLORATORY AREA

BLANCO MV/BASIN DAKOTA

11. COUNTY OR PARISH, STATE

SAN JUAN COUNTY, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other: Spud & casing report - 4- 1/2"
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log Form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

05/04/98 Stage 1: Ran 28 jts of 4-1/2", 9.5#, J-55, ST&C casing. Total footage 1197.74, depth of shoe 7092', depth of collar 7046', Cement with 80 sxs of 35/65 POZ, 8% Gel, 2% CaCl2, 6.25#/sk Gilsonite. Followed by 100 sxs of 50/50 Class B, 4% Gel, .3% FL-52, .3% CD-32, 2% KCl, 6.25#/sk Gilsonite. Displaced with 114 bbl of mud, floats held. Bumped plug @ 06:38 p.m. on 5/3/98 with 1700 psi, pumped 20 bbls mud to regain circ. after opening DV tool.

Stage 2: Stage collar depth 5896.66', manufacturer of stage tool is Weatherford. Cement with 120 sxs of 50/50 POZ Class B, 4% Gel, .3% FL-52, .3% CD-32, 2% KCl, 6.25#/sk Gilsonite. Displace with 95 bbl of mud. Bumped 09:34 p.m. on 5/3/98 with 2500 psi, maintained good returns during the complete operation.

Stage 3: Stage collar depth 4095.37', manufacturer of stage tool is Weatherford. Cement with 65 sxs of 35/65 POZ Class B, 8% Gel, 2% CaCl2, 6.25#/sk Gilsonite. Followed by 50 sxs of 50/50 POZ Class B, 4% Gel, .3% FL-52, .3% CD-32, 2% KCl, 6.25#/sk Gilsonite. Displaced with 66.4 bbls of H2O with muddy returns. Bumped plug @ 12:12 a.m. on 5/4/98 with 2200 psi.

14. I hereby certify that the foregoing is true and correct

SIGNED

Sylvia Johnson

TITLE Sylvia Johnson, As Agent for Conoco Inc. DATE 05/07/98

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

Conditions of approval, if any:

ACCEPTED FOR RECORD

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

FARMINGTON DISTRICT OFFICE

BY

NMOC