Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR

FORM APPROVED Budget/Bureau No. 1004-0135 Expires: March 31, 1993

BUREAU OF LAND MANAGEMENT 5. Lease Designation and Serial No. SF-078996 SUNDRY NOTICES AND REPORTS ON WELLS 6. If Indian, Allottee or Tribe Name Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Lise "APPLICATION FOR PERMIT - " for such proposals 7. If Unit or CA, Agreement Designation SUBMIT IN TRIPLICATE <u>San Juan 32-7 Unit</u> 1. Type of Well X Gas 8. Well Name and No. 2. Name of Operator PSJ 32-7 Unit #220 Phillips Petroleum Company 9. API Well No. 3. Address and Telephone No. 30-045-29567 5525 Highway 64. NBU 3004. Farmington. NM 87401 505-599-3454 10. Field and Pool, or exploratory Area 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) Unit M, 655' FSL & 705' FWL Basin Fruitland Coal Section 5. T31N. R7W 11. County or Parish, State San Juan. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 12. TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent Ahandonment Change of Plans Recompletion New Construction Subsequent Report Plugging Back Non-Routine Fracturing Casing Repair Water Shut-Off Final Abandonment Notice Altering Casing Conversion to Injection NTL-FRA-90-1 Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 99 JUL -2 MM 10: (Description of cement job to fulfill requirements for protection of usable water zones including the Ojo Alamo Formation, as per NTL-FRA-90-1. Time Completed: Date: 6/26/99 Time Started: 1445 hrs 1600 hrs. Hole: 8-3/4" Casing Size: 7", 20#, K-55 New; Casing Set 3614 Turbo Centralizers at 2692', 2649', 2605', 3603', 3566', 3439', 472', Spring Type Centralizers Mud Flush 10 bbls, Spacer 10 Fresh Water. Stage 1: Lead Slurry: 430 sx (903 cf) 35/65 Class H POZ w/5#/sx Gilsonite, 1/4#/sx Cello-flake, 6% gel Tail Slurry: 100 sx (128 cf) Class H w/5#/sx Gilsonite, 1/4#/sx Cello-flake, 0.3% FL-25, 2% CaCl2 Stage 2: Lead Slurry: Tail Slurry: Volume Cement Circulated 15 bbls/sacks 40 Displaced Plug with 144.63 bbls fresh water. 1500 psi. Average Pressure @ 360 psi, Average Rate ____ 5 bpm, Bumped plug with I hereby certiff that the Regulatory_Assistant (This space for Federal of State office use) Approved by ACCEPTED FOR RECORD Conditions of approval, if any: Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States or representations as to any matter within its jurisdiction

* See Instruction on Reverse Side



