Distribution: O+4 (BLM); 1-Accounting; 1- Crystal; 1-File Form 3160-5 **UNITED STATES** FORM APPROVED (June 1990) DEPARTMENT OF THE INTERIOR Budget Bureau No. 1004-0135 BUREAU OF LAND MANAGEMENT Expires: March 31, 1993 Lease Designation and Serial No. SUNDRY NOTICES AND REPORTS ON WELLS SF-078213 Do not use this form for proposals to drill or to deepen or reentry to a different reservoir If Indian, Allottee or Tribe Name Use "APPLICATION FOR PERMIT--" for such proposals SUBMIT IN TRIPLICATE 7. If Unit or CA, Agreement Designation Type of Well liO Gas X Well Well Other Well Name and No. Name of Operator PANTHER No. 1 Merrion Oil & Gas Corporation (14634)API Well No. Address and Telephone No. 610 Reilly Avenue, Farmington, NM 87401-2634 (505) 327-9801 10. Field and Pool, or Exploratory Area Location of Well (Footage, Sec., T., R., M., or Survey Description) Fulcher Kutz P.C. Ext. 990' FSL & 1255' FWL 11. County or Parish, State M Section 25, T30N, R13W (SWSW) San Juan County, New Mexico CHECK APPROPRIATE BOX (s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 12. TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent Abandonment Change of Plans Recompletion **New Construction** Subsequent Report Plugging Back Non-Routine Fracturing Casing Repair Water Shut-Off Final Abandonment Notice Altering Casing Conversion to Injection Other TD & Csg Reports Dispose Water (Note: Report results of multiple completion on Completion or Recompletion Report and Log form.) Describe Proposed or completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* TD 6-1/4" hole at 1810' KB. Condition hole. TOH, LD drill pipe and collars. Ran 4-1/2" guide shoe, 4/14/98 1 shoe joint 43.52'. Insert float on top of shoe joint, 41 joints of 4-12/", 10.5#/ft casing, length 1786.93'. Tag bottom with casing 1815' KB. Circulate bottoms up with rig pump full and good circulation. RU Cementers Inc., pump 10 bbls water ahead of 25 sxs (30 cu.ft.) Class 'G' neat cement, 75 sxs (155 cu.ft.) filler cement and 100 sxs (118 cuft) Class 'G' neat. Lost circulation with 3 bbls left to mix on tail cement. Slowed rate to 1 BPM, dropped plug and displaced with 24 bbls water, pressure during displacement fluctuated up and down then climbed to 2000 psi, 4 bbls short of float, released pressure, float held good. RDMOL - - WOCT. TOC @ 400' by temperature survey. I hereby dertify that the foregoing is true Title Drlg & Prod Manager 4/15/98 Steven S. Dunn (This space for Federal or State office use) Approved By Title Conditions of approval, if any Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false. Figitive purpose or representations as to any matter within its jurisdiction.

NEWS