

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

RICHARDSON OPERATING COMPANY

3. Address and Telephone No. c/o Walsh Engr. & Prod. Corp.

7415 E. Main Farmington, N.M. 87402 505 327-4892

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit N Section 20, T30N, R14W
915'FSL & 1600'FWL

5. Lease Designation and Serial No.

NM-19163

6. If Indian, Allottee or Tribe Name

If Unit or CA, Agreement Designation

8. Well Name and No.

WF Federal 20-1

9. API Well No.

30-045-29649

10. Field and Pool or Exploratory Area

Twin Mounds Sand PC
Basin Fruitland Coal

11. County or Parish, State

San Juan County, N.M.

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

7/24/98 Spud 8-3/4" surface hole. Drill to 129'. Ran 3 jts 7", 20#, casing and set at 128'GL. Cemented with 50 sxs (59 cuft) of C1 "B" with 4% CaCl. Circulated cement to surface. Nipple up BOP and pressure test to 500# - held ok.

7/30/98 TD 6-1/4" hole at 1300'. Ran DIL & Density Logs. Ran 30 jts of 4-1/2", 10.50# K-55 ST&C yellow bank casing and set at 1300'GL = 1247' PBTD. Cemented with 80 sxs (94 cuft) of C1 "B" with 2% metasilicate and 50 sxs (59 cuft) of C1 "B" with 1/4#/sk celloflake. Circulated 2 bbls to surface. Plug down 10:30 AM 7/30/98. Nipple down BOP and install wellhead. Wait on completion.

14. I hereby certify that the foregoing is true and correct

Signed Steve Smethie

Title Petroleum Consultant for ROC

Date 6/22/99

(This space for Federal or State office use)

Approved by _____
Conditions of approval, if any:

Title _____

Date _____

ACCEPTED FOR RECORD

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side

FARMINGTON FIELD OFFICE
BY 8-11-99